

# **NIST Calibration Program Calibration Services Users Guide SP 250 Appendix Fee Schedule 2007**

## ***Calibration Services:***

*Dimensional*

*Mechanical*

*Thermodynamic*

*Optical Radiation*

*Ionizing Radiation*

*Electromagnetic*

*Time and Frequency*

**NIST**

National Institute of  
Standards and Technology  
Technology Administration  
U.S. Department of Commerce

# Table of Contents

## CHAPTER 1

### POLICIES

Introduction .....	4
Types of Services .....	4
Other NIST Measurement Transfer Services .....	4
Criteria for Quality Assurance .....	5
Fees .....	6
Reports of Calibration/Test Results .....	6
Traceability .....	6
NIST Policy on Reporting Measurement Uncertainty .....	7
NIST Policy Regarding Use of Metric (SI) Units .....	7
References to NIST in Advertisements .....	8
Disclaimer .....	8
Questions and Inquires .....	8

## CHAPTER 2

### ORDERING INSTRUCTIONS FOR DOMESTIC CUSTOMERS

Customer Inquires .....	9
Prearrangement and Scheduling .....	9
Purchase Orders .....	9
Shipping, Insurance, and Risk of Loss .....	10
Turnaround Time .....	10
Customer Checklist .....	10

## CHAPTER 3

### SPECIAL INSTRUCTIONS FOR FOREIGN CUSTOMERS

Foreign Inquires .....	12
Criteria for Providing Service .....	12
Special Instructions .....	12
Shipping Charges .....	14

## CHAPTER 4

### DIMENSIONAL MEASUREMENTS

Length Measurements .....	15
Diameter Measurements .....	17
Complex Dimensional Standards .....	18
Optical Reference Planes and Roundness Standards .....	20
Angular Measurements .....	21
Laser Measurements .....	21
Surface Texture .....	22

## CHAPTER 5

### MECHANICAL MEASUREMENTS

Hydrometers .....	23
Volume and Density .....	23
Flow Measurements .....	24
Flow Measurements at Cryogenic Temperatures .....	24
Air Speed Instruments .....	25
Mass Standards .....	26
Force Measurements .....	27

Vibration Measurements.....	28
Acoustic Measurements .....	28

## CHAPTER 6

### THERMODYNAMIC QUANTITIES

Pressure Measurements.....	30
Low Pressure, Vacuum and Leak Measurements .....	30
Laboratory and Industrial-Grade Thermometers.....	31
Thermocouples, Thermocouple Materials, Thermometer Indicators .....	32
Resistance Thermometry .....	34
Radiance Temperature Measurements .....	36
Humidity Measurements.....	37

## CHAPTER 7

### OPTICAL RADIATION MEASUREMENTS

Photometric Measurements.....	38
Optical Properties of Materials Measurements .....	40
Surface Color and Appearance .....	40
Spectroradiometric Measurements.....	41
Radiometric Standards in the Ultraviolet.....	41
Laser and Optoelectronic Components Used with Lasers.....	42

## CHAPTER 8

### IONIZING RADIATION MEASUREMENTS

Radioactivity Sources .....	44
Neutron Sources and Neutron Dosimetry .....	45
Dosimetry of X-Rays, Gamma-Rays .....	45
Dosimetry for High-Dose Applications .....	46

## CHAPTER 9

### ELECTROMAGNETIC MEASUREMENTS

Resistance Measurements .....	48
Impedance Measurements (Except Resistors) .....	50
Voltage Measurements.....	53
Precision Ratio Measurements.....	55
Phase Meters and Standards and VOR Measurements .....	56
Power and Energy Measurements, Low-Frequency .....	57
RF, Microwave and Millimeter-Wave Measurements .....	58
Electromagnetic Field Strength and Antenna Measurements .....	65
Pulse Waveform Measurements.....	66

## CHAPTER 10

### TIME AND FREQUENCY MEASUREMENTS

Broadcast and Measurement Services.....	67
Calibration and Characterization of Oscillators and Amplifiers .....	67
Tests of PM/AM Noise Measurement Systems .....	69

**CHAPTER 11**

**SEMINARS**

NIST Measurement Seminars .....	70
---------------------------------	----

<b>ALPHABETICAL CROSS-INDEX .....</b>	<b>71</b>
---------------------------------------	-----------

# CHAPTER 1

## POLICIES

### A. Introduction

The calibration services of the National Institute of Standards and Technology (NIST) are designed to help the makers and users of precision instruments achieve the highest possible levels of measurement quality and productivity. The services listed in this Fee Schedule constitute the highest order of calibration services available in the United States. They directly link a customer's precision equipment or transfer standards to national and international measurement standards. These services are offered to public and private organizations and individuals alike.

For more specific information, the NIST Calibration Services Users Guide, SP 250, contains data on uncertainty and other technical references. Copies are available upon request or consult our web site (see Section L).

### B. Types of Calibration Services

- Calibration Services
- Special Tests
- Measurement Assurance Programs (MAPs)

NIST provides Calibration Services using well-characterized, stable and predictable measurement processes. NIST calibrates instruments and devices that are metrologically suitable as reference or transfer standards.

Special Tests are either unique or seldom-performed calibrations or measurements requested by the customer.

Measurement Assurance Programs are quality control programs for calibrating a customer's entire measurement system. In a typical MAP, a stable artifact or set of artifacts called transfer standards are first measured by NIST and then sent to a customer's laboratory for a series of measurements. The transfer standards are then returned to NIST for remeasurement, along with the participating laboratory's results. NIST reports its comparative findings to the customer and, when necessary, offers guidance on achieving and maintaining measurement quality. Successful use of a NIST MAP requires that the customer make periodic measurements of in-house check standards to estimate their measurement process uncertainty and to ensure that the measurement process remains in a state of statistical control. Unless a laboratory has a measurement quality assurance program to monitor its own measurement process parameters continuously, there is no value in participating in a MAP. In fact, NIST recommends that its customers establish and use a measurement quality assurance program to monitor their measurement parameters, whether or not they participate in a MAP.

### C. Other NIST Measurement Transfer Services

#### *National Voluntary Laboratory Accreditation Program (NVLAP)*

NIST does not audit or regulate metrology laboratories as part of MAP or other calibration services. Calibration laboratories and testing facilities may be accredited by NIST under the National Voluntary Accreditation Program (NVLAP). The basic procedures and general accreditation requirements of NVLAP are described in NIST Handbook 150. A participating laboratory may voluntarily take steps to improve or assess its measurement process. For further information about NVLAP, contact:

National Voluntary Laboratory Accreditation Program (NVLAP)  
National Institute of Standards and Technology  
100 Bureau Drive, Stop 2140  
Gaithersburg, MD 20899-2140

Telephone: (301) 975-4016  
Fax: (301) 926-2884  
Email: NVLAP@nist.gov  
Internet: www.ts.nist.gov/nvlap

#### ***Standard Reference Materials Group (SRM)***

Calibration assistance and alternative paths for traceability are provided by NIST's Standard Reference Materials Group. Chemical measurement instruments are not calibrated at NIST, but NIST provides suites of Standard Reference Materials (SRMs) for the calibration of the instrument by the user. In addition, NIST provides SRMs for dimensional measurements, thermodynamic property and photometric measurements. For further information about SRMs, contact:

Standard Reference Materials Group (SRM)  
National Institute of Standards and Technology  
100 Bureau Drive, Stop 2300  
Gaithersburg, MD 20899-2300

Telephone: (301) 975-6776  
Fax: (301) 948-3730  
Email: srminfo@nist.gov  
Internet: www.nist.gov/srm

#### ***Standard Reference Data Group (SRD)***

Very few calibrations can be conducted without additional quantitative information related to measurement of physical or chemical properties. NIST develops and publishes evaluated data for technical and scientific applications called Standard Reference Data. For further information about SRD, contact:

Standard Reference Data Group (SRD)  
National Institute of Standards and Technology  
100 Bureau Drive, Stop 2300  
Gaithersburg, MD 20899-2300

Telephone: (301) 975-2208  
Fax: (301) 926-0416  
Internet: www.nist.gov/srd

#### ***Weights and Measures Division (W&M)***

The NIST Weights and Measures Division (W&M) provides measurement services to State and local governments responsible for marketplace transactions involving measurements. State weights and measures laboratories provide alternative sources for calibration services in mass, length, volume, and certain other measurement areas. For further information contact:

Weights and Measures Division (W&M)  
National Institute of Standards and Technology  
100 Bureau Drive, Stop 2600  
Gaithersburg, MD 20899-2600

Telephone: (301) 975-4004  
Fax: (301) 926-0647  
Email: owm@nist.gov  
Internet: www.nist.gov/owm

### **D. Criteria for Quality Assurance**

**All the measurement services listed in this document meet rigorous criteria for quality assurance. Calibration Services and MAPs satisfy the most demanding and explicit requirements in that they are carried out regularly under pre-established and well-defined conditions; the measurement processes involved are well-characterized, stable, and statistically controlled; and quality-control procedures are well-defined and strictly followed. Furthermore, each Calibration Service or MAP is planned and documented to permit continuity of service over time.**

A Special Test is so designated for one or more of the following reasons: (1) the specific type of calibration is seldom requested, thus precluding the maintenance of a large statistical base for characterizing the measurement process; (2) the test request is unique; or (3) the service is still under development—meaning the measurement or calibration methods are still being perfected, or all quality-control documentation not been completed.

## **E. Fees**

NIST recovers the cost of providing calibration services by charging a fee for each calibration performed. The costs of services are published in the Fee Schedule, which is updated and published annually to reflect changes in prices and services. Even so, the cost of many services varies according to your exact calibration specifications; you must therefore provide the technical contact with an exact description of work before receiving a price quote.

**NOTE: Fees for NIST services do not include shipping costs or insurance.**

## **F. Reports of Calibration/Test Results**

Reports on calibrations or other services are the property of the customer. Copies are supplied to other parties only as required by federal law or requested in writing by the customer. The results of calibrations and tests performed by NIST apply only to the specific instrument or standard at the time of test unless otherwise clearly stated.

## **G. Traceability**

The International Vocabulary of Basic and General Terms in Metrology (VIM; 1993) defines traceability as:

The property of the result of measurement or the value of a standard whereby it can be related to stated references, usually national or international standards, through an unbroken chain of comparisons all having stated uncertainties.

Many government regulations and commercial contracts require regulated organizations or contractors to verify that the measurements they are “traceable” and to support the claim of traceability by keeping records that their own measuring equipment has been calibrated by laboratories or testing facilities whose measurements are part of this “unbroken chain.” The purpose of requiring traceability is to ensure that measurements are accurate representations of the specific quantity subject to measurement, within the uncertainty of the measurement.

NIST reports its calibration results, with the measurement values accompanied by the uncertainties associated with the methods, operators, and environment at NIST. Users of these calibration services will make their own measurements with the calibrated instruments or artifacts. In addition to the uncertainty indicated by NIST, other uncertainties are inherent in the instrument, associated with the method or protocol in using the instrument, with the operator of the instrument, and with the physical environment (pressure, temperature, humidity, etc.) in which the measurements are made. Thus, the measurements made with the calibrated instruments or artifacts by organizations outside of NIST have total uncertainty budgets associated with them, only one component of which is the uncertainty reported to them by NIST.

NIST often receives calls to verify the authenticity of a NIST Report of Test number appearing on another organization’s report. Although NIST can verify the authenticity of its report numbers, having an authentic number does not provide complete assurance or evidence that the measurement value provided by another organization is traceable. Not only should there be an unbroken chain of comparisons, each provided measurement should be accompanied by a statement of uncertainty associated with farthest link in the chain from NIST, that is, the last facility providing the measurement value. NIST does not have that information; only the facilities that provided the measurement values to the customer can provide the associated uncertainties and describe the traceability chain.

In summary, to adequately establish an audit trail for traceability, a proper calibration result should include: the assigned value, a stated uncertainty, identification of the standards used in the calibration, and the specification of any environmental conditions of the calibration where correction factors should be applied, if the standard or equipment were to be used under different environmental conditions.

NIST does not define nor enforce traceability except in its NVLAP laboratory accreditation program. Moreover, NIST is not legally required to comply with traceability requirements of other federal agencies; nor do we determine what must be done to comply with another party's contract or regulation calling for such traceability. However, NIST can and does provide technical advice on making measurements consistent with national standards.

Although NIST supports making the user aware of traceability and provides the user with details as to how traceability is established, NIST does not allow the prominent display of its name on proprietary products or in the advertising of them. (See Section J).

## **H. NIST Policy on Reporting Measurement Uncertainty**

To ensure that NIST uncertainty statements are consistent across the organization and with international practice, NIST policy requires that all NIST measurements be accompanied by statements of uncertainty as discussed in NIST Technical Note 1297<sup>1</sup>. That publication is based on the approach to expressing uncertainty in measurements recommended by the International Committee on Weights and Measures (CIPM)<sup>2</sup>. That committee established general rules for evaluating and expressing uncertainty in measurements that are intended to be applicable to a broad spectrum of measurements. Copies of NIST TN 1297 are available upon request (see Section L) or on the web site: [www.physics.nist.gov/Pubs/guidelines/contents.html](http://www.physics.nist.gov/Pubs/guidelines/contents.html).

The American National Standard for Expressing Uncertainty-U.S. Guide to the Expression of Uncertainty of Measurement (ANSI/NCSL Z540-2-1997) is available from the

NCSL International  
2995 Wilderness Place, Suite 107  
Boulder, CO 80301-5404  
303/440-3339  
[www.ncsli.org](http://www.ncsli.org)

NIST reports its calibration results with the measurement values accompanied by the uncertainties associated with the methods, operators, and environment at NIST. Users of these calibration services will make their own measurements with the calibrated instruments or artifacts. In addition to the uncertainty indicated by NIST, other uncertainties are inherent in the instrument, associated with the method or protocol in using the instrument, with the operator of the instrument, and with the physical environment (pressure, temperature, humidity, etc.) in which the measurements are made. Thus, the measurements made with the calibrated instruments or artifacts by organizations outside of NIST have total uncertainty budgets associated with them, only one component of which is the uncertainty reported to them by NIST.

## **I. NIST Policy Regarding Use of Metric (SI) Units**

In accordance with the Metric Conversion Act of 1975 as amended by Section 5164 of the Omnibus Trade and Competitiveness Act of 1988 and as required by related provisions of the Code of Federal Regulations, the National Institute of Standards and Technology (NIST) uses the modern metric system of measurement units (International System of Units–SI) in all publications. When the field of application or the special needs of users of NIST publication require the use of non-SI units, the values of quantities are first stated in the SI units and the corresponding values expressed in non-SI units follow in parentheses. Copies of NIST SP 811<sup>3</sup> are available upon request (see Section L) or on the web site: [www.physics.nist.gov/Pubs/SP811/sp811.html](http://www.physics.nist.gov/Pubs/SP811/sp811.html)

---

<sup>1</sup>Guideline for Evaluating and Expressing the Uncertainty of NIST Measurement Results, NIST Technical Note 1297, 1994 Edition.

<sup>2</sup>Guide to the Expression of Uncertainty in Measurement, International Standards Organization (ISO), 1993 Edition.

<sup>3</sup>Guide for the Use of the International System of Units (SI), NIST Special Publication 811, 1995 Edition.



## **J. Reference to NIST in Advertisements**

The NIST measurement/test results or reports shall not be used to indicate or imply that NIST approves, recommends, or endorses the manufacturer, supplier, or user of any instruments or standards or that NIST in any way guarantees or predicts the future performance of items after calibration or test. No reference shall be made to NIST or to reports or results furnished by NIST in any advertising or sales promotions, which would indicate or imply that NIST approves, recommends, or endorses any proprietary product or proprietary material.

## **K. Disclaimer**

Commercial products, materials, and instruments, are identified in our communications and documents for the sole purpose of adequately describing experimental or test procedures. In no event does such identification imply recommendation or endorsement by NIST of a particular product; nor does it imply that a named material or instrument is necessarily the best available for the purpose it serves.

## **L. Questions and Inquires**

This Fee Schedule is intended to make the task of selecting and ordering an appropriate calibration service as quick and easy as possible. Nevertheless, when questions arise, you should contact NIST for immediate clarification.

General inquires about the NIST calibration services, assistance in determining the availability of services, and requests for complimentary copies of the Calibration Services Users Guide, the Fee Schedule, Guide for the International System of Units (SP 811), and Guidelines for Evaluating and Expressing the Uncertainty of NIST Measurement Results (TN 1297) are to be addressed to:

Calibration Program  
National Institute of Standards and Technology  
100 Bureau Drive, Stop 2300  
Gaithersburg, MD 20899-2300  
Telephone: (301) 975-2092  
Fax: (301) 869-3548  
Email: [calibrations@nist.gov](mailto:calibrations@nist.gov)  
Internet: [www.ts.nist.gov/calibrations](http://www.ts.nist.gov/calibrations)

For technical questions concerning a specific service, directly contact the NIST staff member responsible for that calibration area.

## **CHAPTER 2**

### **ORDERING INSTRUCTIONS FOR DOMESTIC CUSTOMERS**

#### **A. Customer Inquires**

General customer inquires for information or clarifications about the NIST calibration services may be directed as indicated in Section L of Chapter 1.

#### **B. Prearrangements and Scheduling**

Services should be arranged in advance, beginning with direct contact with a NIST technical staff member responsible for the desired service. Use the appropriate technical section of the Users Guide or Fee Schedule to determine whom to contact. This advance communication may answer your questions, clarify the policies and procedures briefly described here, and will permit you to schedule a tentative calibration date. Following the initial communication, you must complete and submit a purchase order and prepare to ship the item according to the procedures described below or agreed upon with the technical contact. If a calibration is scheduled far in advance, the item should not be shipped until shortly before the scheduled date; you must submit the purchase order (complete with the name and number of the desired service) before a firm calibration date can be assigned. When NIST receives your purchase order and assigns a firm service date, your order will be confirmed by the technical contact.

#### **C. Purchase Orders**

Before you ship an item for calibration, send a purchase order to the address listed in the appropriate technical section of the Users Guide or Fee Schedule. The purchase order must:

1. State both the name and number of the NIST service (listed in this Fee Schedule as the “Service ID Number”) being requested. **FAILURE TO INCLUDE THE SERVICE ORDER NUMBER WILL SERIOUSLY IMPEDE SCHEDULING AND SERVICE.**
2. Clearly identify the item(s) being send for calibration, including any serial number(s) or model number(s).
3. Give the name, address, and telephone number of your company’s procurement officer, purchasing agent or other administrative/financial authority.
4. Give the name, address, and telephone number of your company’s technical contact, if different from above.
5. List separately the instructions and address for return shipment, insurance, mailing address for the calibration/test report, and billing address. (Federal or state agency requests for calibration services should be accompanied by a document authorizing that the cost of the service be billed to the agency.)
6. Clearly state any special or necessary conditions of test, such as operating frequency or temperature.
7. Clearly state the customer identification number; i.e., social security number (EIN) for individuals; tax identification number (TIN) for organizations; or agency location code (ALC) for government customers.
8. If the calibration or test report is to be handled in a special manner, give instructions on the purchase order.

**NOTE:** Receipt of orders by NIST does not imply acceptance of any provisions set forth in the order that are contrary to the policy, practice, or regulations of NIST or the U.S. Government. In general, NIST will not sign any affidavits, acknowledgement forms, or other documents that may be required by company policy governing the procurement of goods and services.

## **D. Shipping, Insurance, and Risk of Loss**

Ship the instrument or standard to the mailing address of the technical group providing the service. Please take note that the mailing address is not the same for every technical group.

**Please adhere rigorously to the following procedures:**

1. Ship only items in good repair. Apparatus in disrepair will not be calibrated. If defects are found after calibration has begun, the procedure will be terminated, a report issued, and a charge levied for work completed.
2. Use strong, reusable packing materials and containers marked clearly and indelibly on the outside with the requestor's name, address and the following notation: **REUSABLE CONTAINER, DO NOT DESTROY.**
3. Follow any special shipping procedures given in the technical sections of the Calibration Services Users Guide, particularly those sections covering radiation and dosimetry measurements.
4. Insure the shipments to and from NIST and clearly state the method of return shipment. NIST will not assume liability for loss or damage unless such loss and damage result solely from the negligence of NIST personnel. If return shipment by parcel post is requested or is suitable, NIST will prepay the return shipment but will not insure it. When no shipping or insurance instructions are furnished, NIST will return the shipment by common carrier, collect and uninsured.
5. Shipments to NIST must be at FOB destinations (customer pays for shipping.)
6. Return shipments are sent FOB origin (customer pays for shipping.)

**NOTE: Fees for NIST services do not include shipping cost or insurance.**

## **E. Turnaround Time**

Normal turnaround time for NIST calibration services varies greatly—usually from several weeks to several months depending on the type of service requested, and the service schedule. Some services are only scheduled once or twice a year with appointments made months in advance of the service date. To avoid unnecessary scheduling or administrative delays in the calibration process, always make arrangements with the technical contact for the service you wish to utilize prior to shipping your instrument or artifact to us.

## **F. Customer Checklist**

Please refer to page 11 in this chapter for a Customer Checklist which is intended to assist you in developing the basic information required to process an order for calibration services at NIST.

## *Customer Checklist for Ordering NIST Calibration Services*

Information Obtained from NIST Technical Contact	Comments
NIST Contact (name/telephone)	Provide this information on your purchase order (po)
Is the service available?	Please make sure customer's technical contact discusses service with NIST technical contact before proceeding.
NIST Service Identification Number	Provide this information on your po
Estimated cost of services	Provide this information on your po
Estimated turnaround time	Many calibration services are batched. Find out when to send the instrument.
Special instructions	
Packaging instructions	
Shipping instructions	
Other Precautions	
<b>Information Supplies by the Customer on Purchase Order</b>	
Purchase order number	
Purchase order date	
Customer's tax identification number	
Customer's mailing address	
Customer's billing address	
Name, telephone number, fax number, email address of administrative or procurement contact point at customer's location	
Name, telephone number, fax number, email address of technical contact point at customer's location	
Ship-to address (including NIST technical contact name)	
Return address (for shipment back to customer)	
NIST Service Identification Number	
Estimated cost	
Shipping terms (no FOB destination on return shipment)	
Special instructions from customer's technical contact	

## **CHAPTER 3**

### **SPECIAL INSTRUCTIONS FOR FOREIGN CUSTOMERS**

#### **A. Foreign Inquires**

Foreign customers should address all inquiries to:

Calibration Program  
National Institute of Standards and Technology  
100 Bureau Drive, Stop 2300  
Gaithersburg, MD 20899-2300  
United States of America  
Telephone: (301) 975-2092  
Fax: (301) 869-3548  
Email: [calibrations@nist.gov](mailto:calibrations@nist.gov)  
Internet: [www.ts.nist.gov/calibrations](http://www.ts.nist.gov/calibrations)

**NOTE:** Please clearly indicate your **city** and **country** on all correspondence so that we may promptly respond to your request.

#### **B. Criteria for Providing Service**

Under certain circumstances, NIST is authorized to provide measurement service, including calibration services, for organizations or individuals located outside the United States. However, the Calibration Program must review each request for calibration services to determine if services are available to the requestor's organization in the requestor's country. Foreign customers must provide the following information, in writing, to the Calibration Program (see address above):

1. Identification of the item(s) to be calibrated, including serial and model numbers.
2. A detailed description of the measurements that are needed, or indicate the service identification number.
3. A description of any special requirement/circumstance that might affect the decision to provide the service. For example, will adjustments have to be made to the instrument, or will the time period be restricted in which the device is available for calibration?
4. A complete name and address of the requestor's organization.

#### **C. Special Instructions**

If the request for calibration service is accepted by NIST, the requesting organization will be notified of the cost of service and will be given the contact information for the NIST technical unit that will perform the measurements. The requesting organization must then complete the following steps:

1. Contact the NIST technical staff that will perform the service to determine the time schedule.
2. Send a purchase order to the Calibration Program. Provide complete addresses, including country, for returning the instrument and for mailing the calibration or test report.
3. NIST policy requires prepayment for all NIST calibration services requested by non-U.S. organizations. Before proceeding with any service(s) we will need a check, money order or a bank wire transfer. The prepayment must be for the full amount and be drawn on a U.S. bank. The prepayment methods are as follows:

### **Money Orders & Prepayment Check**

Checks made payable to the National Institute of Standards and Technology (NIST) should be mailed to:

Calibration Program  
National Institute of Standards and Technology  
100 Bureau Drive, Stop 2300  
Gaithersburg, MD 20899-2300

### **Bank Wire Transfers**

Treas NYC (Account is with the Federal Reserve Bank of New York)  
U.S. Dept. of Treasury  
FMS-Banking Operations Branch  
3700 East West Highway, Room 5A05  
Hyattsville, MD 20782  
Phone: 001 (202) 874-6617

ABA# 021030004  
Account # 13060001  
Account Name: TREAS NYC/CTR/BNF=/NIST/AC-13060001

Reference "Calibrations" to enable us to identify your payment. In addition, please be sure to pay any fees assessed for your bank wire transfers; otherwise, they will deduct it from your prepayment wire.

**PLEASE NOTE:** Our account number and name are of critical importance and must be referenced in order for NIST to be properly credited with your payment. It must appear in the precise manner shown to allow for the automated processing and classification of the funds transfer message. In addition, please refer to the NIST invoice number, your purchase order number, your country, and any other pertinent information that would help us identify you payment.

This transfer of funds can only be accomplished by your company going through a U.S. correspondent bank or by having your country's central bank send a swift telecommunication system message to the Federal Reserve Bank. Be sure to cover any processing fees your bank may charge you. Questions on bank wiring can be directed to the NIST Accounts Receivable Office at (301) 975-3880, email: [billing@nist.gov](mailto:billing@nist.gov), or fax at (301) 975-8943.

4. Before shipping the instrument or standard to the appropriate NIST technical unit, you must arrange with a customs broker for entry of the instrument into the U.S. with transportation to and from the port of entry to NIST prepaid. Air freight is most satisfactory. Entry bond is required for instruments not manufactured in the U.S. If arrangements are made with a broker in the country of origin, that broker should, in turn, have a U.S. customs broker in or near the port of entry to arrange for the entry of the instrument and its transportation to NIST. Direct arrangements can be made with customs brokers located in the Washington, DC/Baltimore, Maryland, metropolitan area or in the Denver, Colorado, area, as appropriate. These brokers must arrange for transportation to the port of exit after testing/calibration is completed.

## **D. Shipping Charges**

The calibration costs quoted *do not* include shipping, insurance, or the services of a customs broker. You must arrange and pay for these services separately. For your information, NIST currently uses the following customs brokers:

### **Gaithersburg, Maryland**

Laing International  
P.O. Box 16144  
Washington, DC 20041  
Phone: (703) 471-9279  
Fax: (703) 471-8436

### **Boulder, Colorado**

FedEx Trade Networks  
4725 Paris Street, Suite 200  
Denver, CO 80239  
Phone: (303) 371-9550  
Fax: (303) 373-0850

You are not required to use these customs brokers, but may select a broker of your choice.

## CHAPTER 4

### DIMENSIONAL MEASUREMENTS

#### A. Length Measurements

##### A.1 Gage Blocks

<b><u>Technical Contacts:</u></b> Eric Stanfield (Long blocks) Beverly Connelly (Short blocks) Theodore Doiron	<b><u>Telephone:</u></b> (301) 975-4882  (301) 975-2485  (301) 975-3472	<b><u>Email:</u></b> eric.stanfield@nist.gov  beverly.connelly@nist.gov  theodore.doiron@nist.gov	<b><u>Mailing Address:</u></b> NIST 100 Bureau Drive, Stop 8211 Gaithersburg, MD 20899-8211
---	--	--	--

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

A.1 Gage Blocks		
Service ID Number	Description of Services	Fee (\$)
10010C	Gage Blocks: Set Up Charge, per order	157
10011C	Mechanical Comparisons, per Block (100 mm and shorter)	95
10012C	Mechanical Comparisons, per Block (over 100 mm)	226
10013C	Interferometry, per Block (100 mm and shorter), Maximum 25 Blocks per Order	267
10014C	Interferometry, per Block (over 100 mm), by Special Arrangement	At Cost
10015C	Non-standard size Gage Blocks, by Special Arrangement	At Cost

*Fees are subject to change without notice.*

##### A.2 Line Standards

<b><u>Technical Contact:</u></b> William B. Penzes Thomas W. LeBrun	<b><u>Telephone:</u></b> (301) 975-3477  (301) 975-4256	<b><u>Email:</u></b> wpenzes@nist.gov thomas.lebrun@nist.gov	<b><u>Mailing Address:</u></b> NIST 100 Bureau Drive, Stop 8212 Gaithersburg, MD 20899-8212
---	--	--	--

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

A.2 Line Standards		
Service ID Number	Description of Service	Fee (\$)
10020C	Line Standards: Scales, < 1 m (40 inches), 4 Passes	7943
10021C	Line Standards: Scales, < 1 m (40 inches), 8 Passes	12179
10022C	Line Standards: Stage Micrometer, Per Scale, 30 Intervals, 2 Passes	1323
10023C	Line Standards: Stage Micrometer, Per Scale, 30 Intervals, 4 Passes	1659



10024C	Line Standards: End Standards, < 1 m	7943
10025C	Line Standards: Grid Plates, Less than 60 Intervals, 1 D Linear Calibration	13239

*Fees are subject to change without notice.*

### **A.3 Metal Tapes/Scales and Long Length Artifacts**

<b><u>Technical Contact:</u></b>	<b><u>Telephone:</u></b>	<b><u>Email:</u></b>	<b><u>Mailing Address:</u></b>
Chris Blackburn	(301) 975-6413	chris.blackburn@nist.gov	NIST
Daniel S. Sawyer	(301) 975-5863	daniel.sawyer@nist.gov	100 Bureau Drive, Stop 8211 Gaithersburg, MD 20899-8211

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

<b>A.3 Metal Tapes/Scales and Long Length Artifacts</b>		
Service ID Number	Description of Services	Fee (\$)
10030C	Metal Tapes: Surveying, Oil Gaging and General Purpose; Metal Scales	At Cost
10040S	Special Tests of Long Length Artifacts	At Cost

### **A.4 Step Gages**

<b><u>Technical Contacts:</u></b>	<b><u>Telephone:</u></b>	<b><u>Email:</u></b>	<b><u>Mailing Address:</u></b>
John Stoup	(301) 975-3476	john.stoup@nist.gov	NIST
Theodore Doiron	(301) 975-3472	theodore.doiron@nist.gov	100 Bureau Drive, Stop 8211 Gaithersburg, MD 20899-8211

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

<b>A.4 Step Gages</b>		
Service ID Number	Description of Services	Fee (\$)
11060S	Special Tests of Step Gages	At Cost

## A.5 Other Length Standards

<b>Technical Contacts:</b>	<b>Telephone:</b>	<b>Email:</b>	<b>Mailing Address:</b>
John Stoup	(301) 975-3476	john.stoup@nist.gov	NIST
Theodore Doiron	(301) 975-3472	theodore.doiron@nist.gov	100 Bureau Drive, Stop 8211 Gaithersburg, MD 20899-8211

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

A.5 Other Length Standards		
Service ID Number	Description of Services	Fee (\$)
10050S	Special Tests of Length Standards	At Cost

## B. Diameter and Roundness Measurements

<b>Technical Contacts:</b>	<b>Telephone:</b>	<b>Email:</b>	<b>Mailing Address:</b>
Eric S. Stanfield	(301) 975-4882	eric.stanfield@nist.gov	NIST
Theodore Doiron	(301) 975-3472	theodore.doiron@nist.gov	100 Bureau Drive, Stop 8211 Gaithersburg, MD 20899-8211

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
11010S	Special Tests of Cylindrical Diameter Standards (i.e. Plug and Pin Gages): Set Up Charge, per order	157
11011S	Mechanical comparison, per Gage (25 mm and smaller)	95
11012S	Interferometry, per Gage (50 mm and smaller)	216
11013S	Per Gage (over 50 mm)	At Cost
11014S	Roundness trace, per trace	176
11020C	Measuring Wires for Threads and Gears: Set Up Charge, per order	164
11021C	Single Wire, per wire	98
13020S	Special Tests of Roundness (Sphere and Hemisphere Types) Reversal Method: Radial Deviations from Best Fit Least-Squares Circle at 360 positions	1093
13030S	Special Tests of Roundness Calibration Specimens	At Cost
11030S	Special Tests of Spherical Diameter Standards; Balls: Set Up Charge, per order (applies to mechanical comparison and interferometry)	157
11031S	Mechanical Comparison (51 mm or smaller), Average Diameter, per ball, Expanded Uncertainty, $U \sim \pm 89$ nm to 115 nm	91
11032S	Mechanical Comparison (over 51 mm), Average Diameter, per ball	At Cost
11033S	Interferometry (25 mm or smaller) Average Diameter, per ball, Expanded Uncertainty, $U \sim \pm 30$ nm	465

11034S	Ball Out-of-Roundness: Least-Squares out-of-Roundness and Polar Plots, price per trace (Typically three orthogonal traces for spheres and five traces for CMM calibration spheres)	88/per trace
<b>Special Tests of Internal Diameter Standards: Ring Gages</b>		
11040S	Plain Ring Gages, per ring	743
11050S	Special Tests of Diameter	At Cost

*Fees are subject to change without notice.*

### C. Complex Dimensional Standards

<b><u>Technical Contacts:</u></b>	<b><u>Telephone:</u></b>	<b><u>Email:</u></b>	<b><u>Mailing Address:</u></b>
Dennis Everett (12010C-12070S)	(301) 975-5272	dennis.everett@nist.gov	NIST
John Stoup (12060S)	(301) 975-3476	john.stoup@nist.gov	100 Bureau Drive, Stop 8211
Theodore Doiron	(301) 975-3472	theodore.doiron@nist.gov	Gaithersburg, MD 20899-8211

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
<b>C.1 API Threaded Plug and Ring Gages</b>		
12010C	Spec 5, 1.005 inches to 7 5/8 inches	1702
12011C	Spec 5, 8 5/8 inches to 20 inches	2667
12012C	Buttress Casing, 4 1/2 inches to 9 5/8 inches	2049
12013C	Buttress Casing, 10 inches to 13 3/8 inches	2477
12014C	Buttress Casing, 16 inches to 20 inches	2667
12015C	Line Pipe, 1/8 inch to 6 inches (New)	1702
12016C	Line Pipe, 8 inches to 20 inches (New)	2262
12017C	Extreme Line Casing, 5 inches to 7 inches (New)	2840
12018C	Extreme Line Casing, 5 inches to 7 inches (Used)	1067
12019C	Extreme Line Casing, 7 7/8 inches to 10 inches (New)	3315
12021C	Extreme Line Casing, 7 7/8 inches to 10 inches (Used)	1359
12022C	Spec 7 (Rotary), NC 23-NC 61 (New)	2211
12023C	Spec 7 (Rotary), NC 70 (New)	2442
12024C	Spec 7 (Rotary), 2 3/8 inches to 4 1/2 inches, Reg. (New)	2236
12025C	Spec 7 (Rotary), 5 1/2 inches to 8 5/8 inches, Reg. (New)	2425
12026C	Spec 7 (Rotary), Any Type (Used)	997
12027C	Spec 11B (Sucker Rods) P1, P2 Pin Go P7, P8 Pin Go B1, B2 Box Go (NEW)	1163/per set

12028C	Spec 11B (Sucker Rods) P1, P2 Pin Go P7, P8 Pin Go B1, B2 Box Go <b>(USED)</b>	585/per set
12029C	Spec 11B (Sucker Rods) P3, P4 Pin Cone B3, B4 Box Cone <b>(NEW)</b>	1388/per set
12031C	Spec 11B (Sucker Rods) P3, P4 Pin Cone B3, B4 Box Cone <b>(USED)</b>	533/per set
12032C	Spec 11B (Sucker Rods) P5, P6 Pin Cone B5, B6 Box Cone <b>(NEW)</b>	942/per set
12033C	Spec 11B (Sucker Rods) P5, P6 Pin B5, B6 Box Cone <b>(USED)</b>	485/per set
12050S	Special Test of Threaded Plug and Ring Gages	At Cost
12060S, 11050S	Special Tests of Two– and Three–Dimensional Gages	At Cost
12070S	Special Complex Dimensional Test by Prearrangement	At Cost

*Fees are subject to change without notice.*

## C.2 Sieves

**Technical Contacts:**

Theodore Doiron

**Telephone:**

(301) 975-3472

**Email:**

theodore.doiron@nist.gov

**Mailing Address:**

NIST  
100 Bureau Drive, Stop 8211  
Gaithersburg, MD 20899-8211

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

A.5 Sieves		
Service ID Number	Description of Services	Fee (\$)
10060S	Special Test of Sieves	186

*Fees are subject to change without notice.*

### C.3 Algorithms Testing and Evaluation Program for Coordinate Measuring Systems

**Technical Contact:**

Craig M. Shakarji

**Telephone:**

(301) 975-3545

**Email:**

shakarji@nist.gov

**Mailing Address:**

NIST

100 Bureau Drive, Stop 8260

Gaithersburg, MD 20899-8260

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

A.6 Algorithms Testing and Evaluation Program for Coordinate Measuring Systems		
Service ID Number	Description of Services	Fee (\$)
10070S	Special Test of CMS Software: NIST-generated data sets (basic service)	1731
10071S	Special Test of CMS Software: NIST-generated data sets (per geometry evaluated)	At Cost
10072S	Special Test of CMS Software: NIST-generated data sets, standard level (per geometry evaluated)	881
10080S	Special Test of CMS Software: Customer-generated data sets (basic service)	2289
10081S	Special Test of CMS Software: Customer-generated data sets (per geometry evaluated)	At Cost
10082S	Special Test of CMS Software: Customer-generated data sets, standard level (per geometry evaluated)	943

*Fees are subject to change without notice.*

### D. Optical Reference Planes and Roundness Standards

**Technical Contacts:**

Eric S. Stanfield

Theodore Doiron

**Telephone:**

(301) 975-4882

(301) 975-3472

**Email:**

eric.stanfield@nist.gov

theodore.doiron@nist.gov

**Mailing Address:**

NIST

100 Bureau Drive, Stop 8211

Gaithersburg, MD 20899-8211

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
13010S	Special Tests of Optical Reference Planes (Flats): Optical Flat, $\leq 152$ mm (6"), Per Surface	1328
13011S	Special Tests of Optical Reference Planes (Flats): Optical Flat, 152 mm to 203 mm (8")	1708
13012S	Special Tests of Optical Reference Planes (Flats): Optical Flat, 203 mm to 304 mm	2277
13013S	Special Tests of Optical Reference Planes (Flats): Optical Flat, $\geq 304$ mm (12")	2845
13014S	Special Tests of Optical Reference Planes (Flats): Three Flat Calibration	At Cost
13040S	Special Optical Tests of Complex Forms (coming soon)	

*Fees are subject to change without notice.*

## E. Angular Measurements

**Technical Contacts:**

Bryon S. Faust  
Theodore Doiron

**Telephone:**

(301) 975-4351  
(301) 975-3472

**Email:**

bryon.faust@nist.gov  
theodore.doiron@nist.gov

**Mailing Address:**

NIST  
100 Bureau Drive, Stop 8211  
Gaithersburg, MD 20899-8211

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
14010C	Angle Gage Blocks: Set Up Charge, per order	169
14011C	Angle Block, per block	154
14020S	Special Tests of Optical Polygons	At Cost
14030S	Special Tests of Rotary and Indexing Tables: Every 30°	2193
14031S	Special Tests of Rotary and Indexing Tables: (30°, 5°, 1°) Calibration	4254
14040S	Special Tests of Optical Wedges: Fixed-Angle Wedge	757
14041S	Special Tests of Optical Wedges: Variable-Angle Wedge	At Cost
14050S	Special Angular Measurements, by Prearrangement	At Cost

*Fees are subject to change without notice.*

## F. Laser Measurements

**Technical Contact:**

Jack Stone

**Telephone:**

(301) 975-5638

**Email:**

jack.stone@nist.gov

**Mailing Address:**

NIST  
100 Bureau Drive, Stop 8211  
Gaithersburg, MD 20899-8211

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
14510S	Laser Frequency/Wavelength, Full Calibration	2428
14511S	Quick Check of Frequency/Wavelength at Laboratory Conditions	1290
14020S	Laser Trackers, B89.4.19 Ranging Test (coming soon)	

*Fees are subject to change without notice.*

## G. Surface Texture

**Technical Contact:**

C. Dewey Foreman, Jr.

**Telephone:**

(301) 975-5836

**Email:**

charles.foreman@nist.gov

**Mailing Address:**

NIST

100 Bureau Drive, Stop 8212

Gaithersburg, MD 20899-8212

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
15010C	Roughness Calibration Specimens	1440
15030C	Step Height Measurements	1440
15040S	Surface Roughness and Topography Special Tests	At Cost

*Fees are subject to change without notice.*

## CHAPTER 5

### MECHANICAL MEASUREMENTS

#### A. Hydrometers

**Technical Contacts:**

Sherry Sheckels

John D. Wright

**Telephone:**

(301) 975-5940

(301) 975-5937

**Email:**

sherry.sheckels@nist.gov

john.wright@nist.gov

**Mailing Address:**

NIST

100 Bureau Drive, Stop 8361  
Gaithersburg, MD 20899-8361

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
16010C	Reference Standard Hydrometers	1708
16020S	Hydrometers Special Tests	At Cost

*Fees are subject to change without notice.*

#### B. Volume and Density

**Technical Contacts:**

Sherry Sheckels

John D. Wright

**Telephone:**

(301) 975-5940

(301) 975-5937

**Email:**

sherry.sheckels@nist.gov

john.wright@nist.gov

**Mailing Address:**

NIST

100 Bureau Drive, Stop 8361  
Gaithersburg, MD 20899-8361

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
17010C	Volume Standards	2134
17020C	Volume Standards > 380 L, 2 points	3200
17030C	Volume Standards > 380 L, 5 points	6401
17040S	Volume Special Tests	At Cost

*Fees are subject to change without notice.*



### C. Flow Measurements

**Technical Contacts:**

Gina Kline  
(Gas Flow and Hydrocarbon Flow)

John D. Wright  
(Gas Flow and Water Flow)

Sherry Sheckels  
(Hydrocarbon Flow)

**Telephone:**

(301) 975-4813

(301) 975-5937

(301) 975-5940

**Email**

gina.kline@nist.gov

john.wright@nist.gov

sherry.sheckels@nist.gov

**Mailing Address:**

NIST  
100 Bureau Drive, Stop 8361  
Gaithersburg, MD 20899-8361

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
18010C	Gas Flow Meters	4875
18020C	Water Flow Meters	4953
18030C	Hydrocarbon Flow Meters	4925
18040C	Transfer Standards	At Cost
18050S	Gas Flow Special Tests	At Cost
18060S	Water Flow Special Tests	At Cost
18070S	Hydrocarbon Liquid Flow Special Tests	At Cost

**Fees are subject to change without notice.**

*See 30063S Special Tests for Low-Gas-Flow Instrumentation*

### D. Flow Measurements at Cryogenic Temperatures

**Technical Contact:**

Michael Lewis

**Telephone:**

(303) 497-3458

**Fax:** (303) 497-5224

**Email**

mlewis@boulder.nist.gov

**Mailing Address:**

NIST  
325 Broadway, MC 838.09  
Boulder, CO 80305-3328

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
18800S	Special Tests of Cryogenic Liquid Flow	At Cost

### E. Air Speed Measurements

**Technical Contacts:**

J. Michael Hall  
John D. Wright

**Telephone:**

(301) 975-5947  
(301) 975-5937

**Email:**

j.hall@nist.gov  
john.wright@nist.gov

**Mailing Address:**

NIST  
100 Bureau Drive, Stop 8361  
Gaithersburg, MD 20899-8361

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
19010C	High Air Speed Instruments 1.3 m/s to 67 m/s (3 mph to 150 mph)	2609
19020C	Low Air Speed Instruments 0.3 m/s to 10.2 m/s (15 fpm to 2,000 fpm)	2609
19030S	High Air Speed special Tests	At Cost
19040S	Low Air Speed Special Tests	At Cost

***Fees are subject to change without notice.***

## F. Mass Standards

### **Technical Contacts:**

Vincent Lee  
Zeina J. Jabbour

### **Telephone:**

(301) 975-6453  
(301) 975-4468

### **Email:**

vincent.lee@nist.gov  
zeina.jabbour@nist.gov

### **Mailing Address:**

NIST  
100 Bureau Drive, Stop 8221  
Gaithersburg, MD 20899-8221

### **Administrative and Logistics:**

(301) 975-6624

**Fax:** (301) 417-0514

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
22010C	Weight Set (1 mg to 100 g)	12449
22020C	Weight Set (1 mg to 1 kg)	14317
22030C	Weight Set (2 kg to 30 kg)	6225
22040C	Single Weights (1 mg to 1 kg)	1528
22060C	Single Weights (2 kg to 30 kg)	2025
22080C	Single Weights (> 30 kg to 1200 kg, 2 double substitution weighings)	At Cost
22100C	Single Weights (> 1200 kg to 30,000 kg)	At Cost
22110C	Single Weights (> 30 kg to 1200 kg, calibrated in a weighing design)	At Cost
22130C	Single Weights for Dead Weight Pressure Testers 5.9 kg to 22.7 kg (13 lb to 50 lb)	1064
22140C	Single Weights for Dead Weight Pressure Testers > 22.7 kg (> 50 lb)	At Cost
22150C	Single Weights for Dead Weight Pressure Testers < 5.9 kg (< 13 lb)	809
22170S	Special Mass Measurement Services	At Cost

***Fees are subject to change without notice.***

## G. Force Measurements

**Technical Contacts:**

Rick L. Seifarth  
Thomas W. Bartel  
Kevin L. Chesnutwood

**Telephone:**

(301) 975-6652  
(301) 975-6461  
(301) 975-6653

**Email:**

ricky.seifarth@nist.gov  
tbartel@nist.gov  
kchesnutwood@nist.gov

**Mailing Address:**

NIST  
100 Bureau Drive, Stop 8222  
Gaithersburg, MD 20899-8222

**Administrative and Logistics:**

(301) 975-6624

**Fax:** (301) 417-0514

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
23010C	Force Transducers to 112 540 N (25 300 lbf) 1 mode	2838
23020C	Extra observation	57
23030C	Additional bridges	791
23040C	Force Transducers to 112 540 N (25 300 lbf) 2 modes	4665
23050C	Extra observation	57
23060C	Additional bridges	704
23070C	Force Transducers 112 540 N to 498 201 N (25 300 lbf to 112 000 lbf) 1 mode	3256
23080C	Extra observation	57
23090C	Additional bridges	805
23100C	Force Transducers 112 540 N to 498 201 N (25 300 lbf to 112 000 lbf) 2 modes	6378
23110C	Extra observation	173
23120C	Additional bridges	1843
23130C	Force Transducers 498 205 N to 1 334 467 N (112 000 lbf to 300 000 lbf) 1 mode	6579
23140C	Extra observation	151
23150C	Additional bridges	1152
23160C	Force Transducers 498 205 N to 1 334 467 N (112 000 lbf to 300 000 lbf) 2 modes	10635
23170C	Extra observation	237
23180C	Additional bridges	2073
23190C	Force Transducers 1 334 471 N to 4 448 222 N (300 00 lbf to 1 000 000 lbf)	7959
23200C	Extra observation	173
23210C	Additional bridges	1410

23220C	Force Transducers 1 334 471 N to 4 448 222 N (300 00 lbf to 1 000 000 lbf) 2 modes	12820
23230C	Extra observation	231
23240C	Additional bridges	2517
23250C	Force Transducers over 4 448 222 N (1 000 000 lbf) compression only	At Cost
23260S	Special Tests of Force Transducers	At Cost

*Fees are subject to change without notice.*

#### H. Vibration Measurements

**Technical Contacts:**

David J. Evans  
Kari Harper  
Toni Savoy

**Telephone:**

(301) 975-6637  
(301) 975-6612  
(301) 975-6613

**Email:**

david.evans@nist.gov  
kari.harper@nist.gov  
toni.savoy@nist.gov

**Mailing Address:**

NIST  
100 Bureau Drive, Stop 8220  
Gaithersburg, MD 20899-8220

**Administrative and Logistics:**

Alma Duke (301) 975-6600 alma.duke@nist.gov  
**Fax:** (301) 869-3536

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Freq. Range	Peak Accel.	Fee (\$)
24010C	Transducer Sensitivity	2 Hz to 160 Hz	0.2 g <sub>n</sub> to 2 g <sub>n</sub>	3133
24020C	Transducer Sensitivity	10 Hz to 3500 Hz	2 g <sub>n</sub> to 10 g <sub>n</sub>	5481
24030C	Transducer Sensitivity	10 Hz to 10 kHz	2 g <sub>n</sub> to 10 g <sub>n</sub>	8984
24040S	Shock Measurement	250 Hz to 10 kHz	20 g <sub>n</sub> to 10 000 g <sub>n</sub>	At Cost
24050S	Transducer Sensitivity	3 kHz to 20 kHz	4 g <sub>n</sub> to 200 g <sub>n</sub>	At Cost
24060S	Special Vibration Tests, by Prearrangement			At Cost

*Fees are subject to change without notice.*

#### I. Acoustic Measurements

**Technical Contacts:**

Victor Nedzelnitsky  
Randall P. Wagner  
David J. Evans

**Telephone:**

(301) 975-6638  
(301) 975-6619  
(301) 975-6637

**Email:**

vnedzelnitsky@nist.gov  
randall.wagner@nist.gov  
david.evans@nist.gov

**Mailing Address:**

NIST  
100 Bureau Drive, Stop 8221  
Gaithersburg, MD 20899-8221

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
25010C	Pressure Response: WE Type 640AA microphones or equivalent (e.g., Tokyo Riko Type ECL MR103; Bruel & Kjaer Type 4160, Bruel & Kjaer Types 4144 or 4132 with DB0111 adapter), 50 Hz to 10,000 Hz	5407

Service ID Number	Description of Services	Fee (\$)
25020C	Pressure Response: WE Type 640AA microphones or equivalent (e.g., Tokyo Riko Type ECL MR103; Bruel & Kjaer Type 4160; Bruel & Kjaer Types 4144 or 4132 with DB0111 adapter), 50 Hz to 20,000 Hz	6539
25030C	Pressure Response: Tokyo Riko Type ECL MR112, Bruel & Kjaer Type 4134, or equivalent half-inch microphones, 50 Hz to 10,000 Hz	6211
25040C	Pressure Response: Tokyo Riko Type EC MR112, Bruel & Kjaer Type 4134, or equivalent half-inch microphones, 50 Hz to 20,000 Hz	7827
25050C	Free-Field Response: Tokyo Riko Type ECL MR112, Bruel & Kjaer Types 4133, 4134, 4165, 4166, 4180, or equivalent half-inch microphones, 2,500 Hz to 20,000 Hz	6628
25060S	Special Test of Acoustic Devices	At Cost
25070S	Special Tests of Earphones	5713

*Fees are subject to change without notice.*

## CHAPTER 6

### THERMODYNAMIC QUANTITIES

#### A. Pressure Measurements

<b><u>Technical Contacts:</u></b> Douglas A. Olson (All Services) R. Gregory Driver (pneumatic gages) (29010C, 29030C, 29035C, 29040S)	<b><u>Telephone:</u></b> (301) 975-2956 (301) 975-4832	<b><u>Email:</u></b> dolson@nist.gov rdriver@nist.gov	<b><u>Mailing Address:</u></b> NIST 100 Bureau Drive, Stop 8364 Gaithersburg, MD 20899-8364
--	--	---	--

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
29010C	Deadweight Piston Gages	6669
29020C	Controlled Clearance Piston Gages	At Cost
29030C	Pressure Gages and Transducers	At Cost
29035C	Non-mercurial Barometers and Manometers	At Cost
29040S	Special Tests of Pressure Gages	At Cost

*Fees are subject to change without notice.*

#### B. Vacuum, Low Pressure and Leak Measurements

<b><u>Technical Contacts:</u></b> Jay Hendricks (30010C- 30025C, 30040S) Patrick J. Abbott (30029C- 30038C, 30050S, 30060S-30062C)	<b><u>Telephone:</u></b> (301) 975-4836 (301) 975-4838	<b><u>Email:</u></b> jay.hendricks@nist.gov patrick.abbott@nist.gov	<b><u>Mailing Address:</u></b> NIST 100 Bureau Drive, Stop 8364 Gaithersburg, MD 20899-8364
--	--	---	--

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

**NOTE:** 1 Torr = 133.322 Pa

Service ID Number	Description of Services	Fee (\$)
30010C	One Low-Pressure Transducer Absolute or Differential Relative to Vacuum	4386
30011C	Additional Transducer (Cost per Unit)	4185
30020C	One Differential Low-Pressure Transducer Relative to near Atmospheric Pressure	4909
30021C	Additional Transducers (Cost per Unit)	4408
30025C	Piston Gauges versus and Ultrasonic Interferometer Manometer	At Cost
30029C	Spinning Rotor Gages, below 0.1 Pa, Nitrogen Gas with NIST Controller	4369
30030C	Spinning Rotor Gages, below 0.1 Pa, Nitrogen Gas Customer Controller with IEEE-488	4369
30031C	Spinning Rotor Gages, below 0.1 Pa, Additional Gas	5423

30032S	Special Test of Spinning Rotor Gages, Transition Range (above 0.1 Pa)	At Cost
30034C	Ionization Gages, $10^{-4}$ Pa to $10^{-1}$ Pa, Nitrogen Gas	5087
30035C	Ionization Gages, $10^{-5}$ Pa to $10^{-1}$ Pa, Nitrogen Gas	6176
30036C	Ionization Gages, $10^{-7}$ Pa to $10^{-1}$ Pa, Nitrogen Gas	7031
30037C	Ionization Gages, Additional Filament or Gas for Above Tests	At Cost
30038C	Ionization Gages, NIST Supplied Gage Tube for Above Tests	303
30040S	Special Tests of Low-Pressure Gages	At Cost
30050S	Special Tests of Vacuum Gages	At Cost
30060S	Special Tests of Leak Artifacts ( $10^{-13}$ mol/s to $10^{-6}$ mol/s)	At Cost
30061C	Helium Leaks, Primary Calibration ( $10^{-13}$ mol/s to $10^{-6}$ mol/s)	5852
30062C	Helium Leaks, Comparison Calibration ( $10^{-13}$ mol/s to $10^{-9}$ mol/s)	4582
30063S	Special Tests of Low-Gas-Flow Instruments	At Cost

*Fees are subject to change without notice.*

**NOTE:** Due to the time and effort required preparing vacuum instrumentation for calibration it is particularly important that they be known to be in proper operating condition when they are submitted to NIST. Equipment will be inspected upon receipt and the customer notified of any obvious damage. If the schedule permits, we will cooperate with the customer's efforts to repair or replace damaged equipment so that the calibration of their equipment can proceed. However, concealed damage or operational deficiencies most likely will not be detected before the instrument is operating on the vacuum system or the calibration has started; in such cases, **if the equipment cannot be calibrated, we will charge 20% of the regular calibration fee for low-pressure transducers and 30% of the regular fee for spinning rotor and ionization gages.**



### C. Laboratory and Industrial-Grade Thermometers

**Technical Contact:**

C. Dawn Cross

**Telephone:**

(301) 975-4822

**Email:**

dawn.cross@nist.gov

**Mailing Address:**

NIST

100 Bureau Drive, Stop 8363  
Gaithersburg, MD 20899-8363

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

**NOTE:** The minimum number of test points per thermometer is two. Fahrenheit ranges are not direct conversions of the Celsius ranges.

Service ID Number	Description of Services	Fee (\$)
31010C	Laboratory Thermometers (0 °C to 150 °C) (32 °F to 300 °F)	426/pt
31020C	Laboratory Thermometers (151 °C to 315 °C) (301 °F to 600 °F)	520/pt
31030C	Laboratory Thermometers (316 °C to 550 °C) (601 °F to 1022 °F)	520/pt
31040C	Laboratory Thermometers (-1 °C to -110 °C) (31 °F to -166 °F)	520/pt
31050C	Laboratory Thermometers (Liquid N <sub>2</sub> ) (-196 °C or -321 °F)	426/pt
31100C	Quantity Tests of Liquid-In-Glass Thermometers	At Cost
31110S	Special Tests of Industrial Platinum Resistance Thermometers, Thermistor Thermometers, Digital Thermometers and Other Types of Thermometers (0 °C to 150 °C) (32 °F to 300 °F)	426/pt
31120S	Special Tests of Industrial Platinum Resistance Thermometers, Thermistor Thermometers, Digital Thermometers and Other Types of Thermometers (151 °C to 315 °C) (301 °F to 600 °F)	520/pt
31130S	Special Tests of Industrial Platinum Resistance Thermometers, Thermistor Thermometers, Digital Thermometers and Other Types of Thermometers (316 °C to 550 °C) (601 °F to 1022 °F)	520/pt
31140S	Special Tests of Industrial Platinum Resistance Thermometer, Thermistor Thermometers, Digital Thermometers and Other Types of Thermometers (-1 °C to -110 °C) (31 °F to -166 °F)	520/pt
31150S	Special Tests of Industrial Platinum Resistance Thermometers, Thermistor Thermometers, Digital Thermometers and Other Types of Thermometers (Liquid N <sub>2</sub> ) (-196 °C or -321 °F)	426/pt
31170S	Special Tests of Calorimetric Thermometers	1652
31180S	Special Test of Beckmann Thermometers	1709
31190S	Additional copy of Table from Results of 31110S-31150S at a Later Date	381
31200S	Preliminary Examination of Ineligible Thermometer	85
31250S	Additional Copy of Report	85
31260S	Special Thermometry Services, by Prearrangement	At Cost

*Fees are subject to change without notice.*

**D. Thermocouples, Thermocouple Materials, Thermometer Indicators****Technical Contacts:**

Christopher W. Meyer (32010C-32150S)

Karen Garrity

(32010C-32101C, 32150S)

C. Dawn Cross

(32110C-32147C)

**Telephone:**

(301) 975-4825

(301) 975-4818

(301) 975-4822

**Email:**

cmeyer@nist.gov

kgarrity@nist.gov

dawn.cross@nist.gov

**Mailing Address:**

NIST

100 Bureau Drive, Stop 8363

Gaithersburg, MD 20899-8363

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

<b>COMPARED CALIBRATIONS, TEMPERATURE MEASURED WITH THERMOCOUPLE</b>						
Service ID Number	TC Type	Temp Range °C	Points	Min. Length (mm)	Temp. (°C)	Fee (\$)
32010C	S	0 to 1450	1 °C or 1 °F Interv. Table	700	0 to 1100 1450	1191
32020C	R	0 to 1450	1 °C or 1 °F Interv. Table	700	0 to 1100 1450	1191
32030C	B	0 to 1750	1 °C or 1 °F Interv. Table	1000	0 to 800 800 to 1100 1450 1750	1789
32031C	B	800 to 1750	1 °C or 1 °F Interv. Table	1000	800 to 1100 1450 1750	1191
32040C	E	0 to 1000	4 to 15	700	0 to 1000	1191
32041C	J	0 to 760	4 to 15	700	0 to 760	1191
32042C	K	0 to 1100	4 to 15	700	0 to 1100	1191
32043C	N	0 to 1100	4 to 15	700	0 to 1100	1191
32044C	T	0 to 400	4 to 15	700	0 to 400	1191
32050C	Comparison calibration, two point minimum, per point, for all items above					550/pt
32060C	Each additional table of results at 1 °C or 1 °F intervals, for type S, R, or B at later date					318
32061C	Each additional table of results at 1 °C or 1 °F intervals, for type S, R, or B at time of test					189
32070C	Thermocouple materials tested against Pt Thermoelectric standard, 4 to 15 points, 700 mm minimum lengths					1191

CALIBRATION AT METAL FREEZING POINTS, MINIMUM TC WIRE DIAMETER 0.4 mm, FREEZING POINT DETERMINATION AT Au, Ag, Al, AND Zn						
Service ID Number	TC Type	Temp Range °C	Points	Min. Length (mm)	Temp. (°C)	Fee (\$)
32090C	S or R	0 to 1450	Table 1 °C or 1 °F Interv. And equations to generate table	1000	at freezing points  0 to 1100 1450	3007
32091C	Type S or T, freezing point determination, per point, two point minimum					1064
CALIBRATION OF DIGITAL THERMOMETER INDICATOR OR PORTABLE POTENTIOMETER						
32100C	Indicator or Potentiometer, first dial or range					901
32101C	Indicator or Potentiometer, each additional dial or range					503
COMPARISON CALIBRATION OF THERMOCOUPLES OR THERMOCOUPLE MATERIALS TESTED AGAINST Pt THERMOELECTRIC STANDARD, TEMPERATURE MEASURED WITH STANDARD PLATINUM RESISTANCE THERMOMETER, MINIMUM TC WIRE LENGTH 1.0 M, TWO POINT MINIMUM						
32110C	Range -110 °C to 315 °C and Liquid N <sub>2</sub> (-196 °C) or -166 °F to 600 °F and Liquid N <sub>2</sub> (-321 °F), Expanded Uncertainty 0.4 °C					615/pt
32120C	316 °C to 550 °C or 601 °F to 1022 °F, Expanded Uncertainty 0.5 °C					615/pt
Table at one degree intervals for Type T thermocouple for any of the following options: (The cost of the table will be in addition to the calibration per point covered under fee schedule services numbered 32110C-32120C).						
32141C	Option 1: Table from -196 °C to +300°C (-321 °F to +572 °F), calibration points at (-196, -110, 250, +100, +200, +300) °C					539
32142C	Option 2: Table from -196 °C to +100 °C (-321 °F to +212 °F), calibration points at (-196, -110, 250, +50, +100) °C					539
32143C	Option 3: Table from -110 °C to +300 °C (-166 °F to +572 °F), calibration points at (-110, 250, +100, +200, +300) °C					539
32144C	Option 4: Table from -110 °C to +100 °C (-166 °F to +212 °F), calibration points at (-110, 250, +50, +100) °C					539
32145C	Option 5: Table from 0 °C to 300 °C (32 °F to +572 °F), calibration points at (+100, +200, +300) °C					539
32146C	Option 6: Table from -110 °C to 0 °C (-166 °F to +32 °F), calibration points at (-110, 250) °C					539
32147C	Option 7: Table from -196 °C to 0 °C (-321 °F to +32 °F), calibration points at (-196, -110, 250) °C					539
32150S	Special Tests of Thermocouples and Thermocouple Materials					At Cost

*Fees are subject to change without notice.*

**NOTE:** Due to the extra time involved in calibrating sheathed thermocouples, a surcharge of 20% of the cost of calibrating bare-wire thermocouples will be added to the relevant fees listed above.

## E. Resistance Thermometry

### Technical Contacts:

Weston L. Tew (0.65 K to 84 K)  
Gregory F. Strouse  
(83K to 962 °C)

### Telephone:

(301) 975-4811  
(301) 975-4803

### Email:

wtew@nist.gov  
gstrouse@nist.gov

### Mailing Address:

NIST  
100 Bureau Drive, Stop 8363  
Gaithersburg, MD 20899-8363

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
33010C	Capsule SPRT (13.8 K to 30 °C) e-H <sub>2</sub> to Ga	10453
33020C	Capsule SPRT (13.8 K to 157 °C) e-H <sub>2</sub> to In	10453
33030C	Capsule SPRT (13.8 K to 232 °C) e-H <sub>2</sub> to Sn	11471
33031C	Capsule SPRT (24.5 K to 30 °C) Ne to Ga	8208
33032C	Capsule SPRT (24.5 K to 157 °C) Ne to Ga	8651
33033C	Capsule SPRT (24.5 K to 232 °C) Ne to Sn	9669
33040C	Capsule SPRT(54 K to 30 °C) O <sub>2</sub> to Ga	7340
33050C	Capsule SPRT (54 K to 157 °C) O <sub>2</sub> to In	7783
33060S	Capsule SPRT (54 K to 232 °C) O <sub>2</sub> to Sn	9557
30065S	Capsule SPRT (83 K to 0.01 °C) Ar to TPW	At Cost
30070C	Capsule SPRT (83 K to 30 °C) Ar to Ga	7199
33080C	Capsule SPRT (83 K to 157 °C) Ar to In	7199
33090C	Capsule SPRT (83 K to 232 °C) Ar to Sn	9143
33100C	Capsule SPRT (0 °C to 30 °C) TPW to Ga	2745
33110C	Capsule SPRT (0 °C to 157 °C) TPW to In	3188
33120C	Capsule SPRT (0 °C to 232 °C) TPW to Sn	4962
33130C	Capsule SPRT (234 K to 30 °C) Hg to Ga	5039
33140C	Rhodium-Iron or Platinum-Cobalt Resistance Thermometers (0.65 K to 24.6 K)	11007
33141C	Rhodium-Iron or Platinum-Cobalt Resistance Thermometers (0.65 K to 83.8 K)	13729
33142C	n-Type Germanium Resistance Thermometers (0.65 K to 24.6 K)	12607
33150C	Long Stem SPRT (83 K to 0.01 °C) Ar to TPW	3642
33160C	Long Stem SPRT (83 K to 30 °C) Ar to Ga	4311
33170C	Long Stem SPRT (83 K to 157 °C) Ar to In	5020
33180C	Long Stem SPRT (83 K to 232 °C) Ar to Sn	5642
33190C	Long Stem SPRT (83 K to 420 °C) Ar to Zn	6755

33200C	Long Stem SPRT (83 K to 661 °C) Ar to Al	7907
33210C	Long Stem SPRT (234 K to 30 °C) Hg to Ga	2991
33220C	Long Stem SPRT (234 K to 157 °C) Hg to In	3925
33230C	Long Stem SPRT (234 K to 232 °C) Hg to Sn	4811
33240C	Long Stem SPRT (234 K to 420 °C) Hg to Zn	5831
33250C	Long Stem SPRT (234 K to 661 °C) Hg to Al	6944
33260C	Long Stem SPRT (0 °C to 30 °C) TPW to Ga	1467
33270C	Long Stem SPRT (0 °C to 157 °C) TPW to In	2117
33280C	Long Stem SPRT (0 °C to 232 °C) TPW to Sn	2792
33290C	Long Stem SPRT (0 °C to 420 °C) TPW to Zn	3679
33300C	Long Stem SPRT (0 °C to 661 °C) TPW to Al	4962
33310C	Long Stem SPRT (0 °C to 962 °C) TPW to Ag	10001
33320C	Additional Copy of Table from Results of 33010C-33310C at Time of Test	127
33330C	Additional Copy of Table from Results of 33010C-33310C at a Later Date	376
33340C	Minimum Charge for Unsuitable Thermometer	608
33350S	Special Tests of Resistance Thermometers	At Cost
33355S	Special Tests of Cryogenic Resistance Thermometers	At Cost
33360S	Special Tests of Thermometric Fixed-Point Devices	At Cost
33370M	Measurement Assurance Program for Temperature 83 K to 420 °C (Ar to Zn)	23447
33380M	Measurement Assurance Program for Temperature 83 K to 661 °C (Ar to Al)	25796

*Fees are subject to change without notice.*

## F. Radiance Temperature Measurements

**Technical Contact:**

Charles E. Gibson

**Telephone:**

(301) 975-2329

**Email:**

cgibson@nist.gov

**Mailing Address:**

NIST

100 Bureau Drive, Stop 8441

Gaithersburg, MD 20899-8441

**Fax:** (301) 869-5700

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
<b>Calibration reports are issued giving the radiance temperature of the blackbody at 655.48 nm versus the scale reading, output current, or output voltage</b>		
35010C	Radiance Temperature Standard, Disappearing Filament Optical Pyrometer (800 °C to 2400 °C, 4 to 12 points, 1 range)	8353
35020C	Radiance Temperature Standard, Disappearing Filament Optical Pyrometers (each additional range up to 4200 °C, only available with 35010C)	6033
35040C	Radiance Temperature Standard, Disappearing Filament Optical Pyrometer (800 °C to 4200 °C, 1 range 3 or fewer points)	4177
<b>Calibration reports are issued giving the radiance temperature of the lamp at 655.48 nm versus the lamp current</b>		
35050C	Radiance Temperature Standard, Tungsten Strip Lamp (800 °C to 2300 °C, 6 to 16 points)	11602
35051C	Recalibration of Tungsten Strip Lamp (800 °C to 2300 °C, 6 to 16 points)	9746
35060C	Radiance Temperature Standard, Tungsten Strip Lamp (800 °C to 2300 °C, 5 or fewer points)	7426
35061C	Recalibration of Tungsten Strip Lamp (800 °C to 2300 °C, 5 or fewer points)	5569
<b>Calibration reports are issued giving the radiance temperature of the reference blackbody at 655.48 nm, 900 nm or 1000 nm versus the display reading, output current, or output voltage</b>		
35070S	Special Tests of Radiation Thermometers (800 °C to 2700 °C)	At Cost
35071C	Radiance Temperature Standard, Radiation Thermometer (800 °C to 2700 °C, 6 to 20 points)	8817
35072C	Radiance Temperature Standard, Radiation Thermometer (800 °C to 2700 °C, 5 or fewer points)	4641
<b>Calibration reports are issued giving the thermodynamic temperature of the reference blackbody versus the display reading, output current, or output voltage.</b>		
35080S	Special Tests of Radiation Thermometers (15 °C to 900 °C)	At Cost
35081C	Radiance Temperature Standard, Radiation Thermometer (15 °C to 70 °C, 3 points)	4641
35082C	Radiance Temperature Standard, Radiation Thermometer (70 °C to 170 °C, 3 points)	4641

35083C	Radiance Temperature Standard, Radiation Thermometer (400 °C to 700 °C, 3 points)	4641
35084C	Radiance Temperature Standard, Radiation Thermometer (700 °C to 900 °C, 3 points)	4641
<b>Calibration reports are issued giving the thermodynamic temperature of the reference blackbody versus the test blackbody source display reading.</b>		
35090S	Special Tests of Blackbody Sources (15 °C to 900 °C)	At Cost
<b>Calibration reports are issued giving heat flux at the sensor surface versus the output voltage.</b>		
35100S	Special Tests of Radiative Heat Flux Sensors	At Cost
35101C	Radiative Heat Flux Sensors (1 W/cm <sup>2</sup> to 5 W/cm <sup>2</sup> , 9 points, Gardon and Schmidt-Boelter type sensors)	3712
35102C	Additional Radiative Heat Flux Sensor (same model as 35101C)	2785

*Fees are subject to change without notice.*

**Calibration Schedule:** Requests for calibration services are scheduled after receipt of a purchase order.

#### G. Humidity Measurements

**Technical Contacts:**

Peter H. Huang  
Joseph T. Hodges  
Gregory E. Scace

**Telephone:**

(301) 975-2621 or 2626  
(301) 975-2605  
(301) 975-2626

**Email:**

phuang@nist.gov  
jhodges@nist.gov  
gregory.scace@nist.gov

**Mailing Address:**

NIST  
100 Bureau Drive, Stop 8363  
Gaithersburg, MD 20899-8363  
**Fax:** (301) 548-0206

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
36010C	Dew-Point Hygrometers (+25 °C to –15 °C)	6218
36020C	Dew-Point Hygrometers (-70 °C to –15 °C)	11753
36030C	Electric Hygrometers	At Cost
36040C	Electrolytic Hygrometers	At Cost
36050C	Aspirated Hygrometers	At Cost
36060C	Pneumatic Bridge Hygrometers	At Cost
36070S	Special Tests of Humidity	At Cost

*Fees are subject to change without notice.*

## CHAPTER 7

### OPTICAL RADIATION MEASUREMENTS

#### A. Photometric Measurements

**Technical Contact:**  
Cameron Miller

**Telephone:**  
(301) 975-4713

**Email:**  
c.miller@nist.gov

**Mailing Address:**  
NIST  
100 Bureau Drive, Stop 8442  
Gaithersburg, MD 20899-8442  
**Fax:** (301) 840-8551

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
37010C	Luminous Intensity and Color Temperature Standard Lamps	4807
37020S	Special Tests for luminous Intensity and Color Temperature of Submitted Lamps	At Cost
37030C	Color Temperature Standard Lamps	3878
37040C	Each Additional Color Temperature for 37030C	929
37050S	Special Tests for Color Temperature of Submitted Lamps	At Cost
37060S	Special Tests for Total Luminous Flux of Submitted Incandescent Lamps and Florescent Lamps	At Cost
37070C	Opal Glass Luminance Coefficient Standards	3554
37080S	Special Tests for Submitted Luminance Sources and Transmitting Diffusers	At Cost
37090S	Special Tests for Photometers, Illuminance Meters and Luminance Meter	At Cost
37100S	Special Photometric Tests	At Cost
37110S	Special Tests for Submitted Flashing-Light Photometers	At Cost
37120S	Special Tests for Color Measuring Instruments for Displays	At Cost
37130S	Special Tests for Luminous Intensity and Luminous Flux of LEDs	At Cost

*Fees are subject to change without notice.*



## B. Optical Properties of Materials Measurements

### Technical Contacts:

David W. Allen  
Maria E. Nadal  
(38010C-38091S)

### Telephone:

(301) 975-3680  
(301) 975-4632

### Email:

david.allen@nist.gov  
maria.nadal@nist.gov

### Mailing Address:

NIST  
100 Bureau Drive, Stop 8442  
Gaithersburg, MD 20899-8442  
**Fax:** (301) 840-8551

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
38010C	Spectral Transmittance Filters (Cobalt Blue Glass)	4189
38020C	Spectral Transmittance Filters (Copper Green Glass)	4189
38030C	Spectral Transmittance Filters (Carbon Yellow Glass)	4189
38040C	Spectral Transmittance Filters (Selenium Orange Glass)	4189
38050C	Wavelength Standards (Holmium Oxide Glass)	3436
38051C	Wavelength Standards	3436
38060S	Special Tests of Spectral Reflectance	At Cost
38061S	Special Tests of Spectral Transmittance	At Cost

*Fees are subject to change without notice.*

## C. Surface Color and Appearance

### Technical Contacts:

Maria E. Nadal  
Robert Bousquet

### Telephone:

(301) 975-4632  
(301) 975-5371

### Email:

maria.nadal@nist.gov  
robert.bousquet@nist.gov

### Mailing Address:

NIST  
100 Bureau Drive, Stop 8442  
Gaithersburg, MD 20899-8442  
**Fax:** (301) 840-8551

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
38090S	Specular Gloss	At Cost
38091S	Special Test of 0°/45° Surface Color	At Cost
38100C	X-Ray Film Step Tablet Transmission Density Standard	867
38110C	Recalibration of an X-Ray Film Step Tablet Transmission Density Standard	At Cost
38120C	Photographic Film Step Tablet Transmission Density Standard	1060
38130C	Recalibration of a Photographic Film Step Tablet Transmission Density Standard	At Cost

*Fees are subject to change without notice.*

## D. Spectroradiometric Measurements

### Technical Contacts:

Charles E. Gibson  
(39010C-39060S)

Jeanne M. Houston  
(39071C-39081S)

Thomas C. Larason  
(39080S, 39081S, 39100S)

George Eppeldauer (39090S)

### Telephone:

(301) 975-2329

(301) 975-2327

(301) 975-2334

(301) 975-2338

### Email:

cgibson@nist.gov

jeanne.houston@nist.gov

tlarason@nist.gov

geppeldauer@nist.gov

### Mailing/Shipping Address:

NIST

100 Bureau Drive, Stop 8441

Gaithersburg, MD 20899-8441

**Fax:** (301) 869-5700

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

D.1 Spectroradiometric Source Measurements		
Service ID Number	Description of Services	Fee (\$)
<b>NIST calibrates and issues a type 30A/T24/13 tungsten strip lamp with a mogul bi-post base.</b>		
39010C	Spectral Radiance Standard, Tungsten Strip Lamp (225 nm to 2400 nm) (other spectral ranges are available under no. 39060S)	16141
<b>NIST calibrates customer supplied integrating sphere sources and maps the source aperture.</b>		
39020C	Spectral Radiance Standard, Integrating Sphere Source (300 nm to 1000 nm in 25 nm steps)	9097
39021C	Spectral Radiance Standard, Integrating Sphere Source (300 nm to 2400 nm in 25 nm steps)	12809
<b>NIST calibrates and issues an 1000 W, tungsten quartz-halogen lamp mounted in a medium bi-post base. The calibrations are performed at 50 cm.</b>		
39030C	Spectral Irradiance Standard, 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 450 nm)	11951
39031C	Recalibration of 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 450 nm)	8447
39032C	Spectral Irradiance Standard, 1000 W Tungsten Quartz-Halogen Lamp (350 nm to 800 nm)	11951
39033C	Recalibration of 1000 W Tungsten Quartz-Halogen Lamp (350 nm to 800 nm)	8447
39040C	Spectral Irradiance Standard, 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 1600 nm)	14945
39041C	Recalibration of 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 1600 nm)	11511
39045C	Spectral Irradiance Standard, 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 2400 nm)	17421
39046C	Recalibration of 1000 W Tungsten Quartz-Halogen Lamp (250 nm to 2400 nm)	14295
<b>NIST calibrates and issues a 30 W deuterium arc lamp mounted in a medium bi-post base.</b>		
39050C	Spectral Irradiance Standard, 30W Deuterium Arc Lamp (200 nm to 400 nm)	15236
39051C	Recalibration of 30 W Deuterium Arc Lamp (200 nm to 400 nm)	11232
39060S	Special Tests of Radiometric Sources	At Cost

<b>D.2 Spectroradiometric Detector Measurements</b>		
39071C	UV Silicon Photodiodes	5083
39072C	Recalibration of UV Silicon Photodiodes	3961
39073C	Visible to NIR Silicon Photodiodes	5175
39074C	Recalibration of Visible to NIR Silicon Photodiodes	3961
39075S	Special Tests of NIR Photodiodes	At Cost
39077C	UV to Near-Infrared Silicon Photodiodes (Hamamatsu S2281)	6166
39078C	Recalibration of UV to Near-Infrared Silicon Photodiodes (Hamamatsu S1337-1010BQ or S2281)	4951
39080S	Special Tests of Radiometric Detectors	At Cost
39081S	Special Tests of Photodetector Responsivity Spatial Uniformity	At Cost
39090S	Special Tests of IR Detectors	At Cost
39100S	Special Tests of Irradiance Detectors	At Cost

*Fees are subject to change without notice.*

#### **E. Radiometric Standards in the Ultraviolet**

**Technical Contact:**

Robert E. Vest

**Telephone:**

(301) 975-3992

**Email:**

rvest@nist.gov

**Mailing Address:**

NIST

100 Bureau Drive, Stop 8411  
Gaithersburg, MD 20899-8411

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

<b>Standard Detectors in the Far Ultraviolet</b>		
Service ID Number	Description of Services	Fee (\$)
40510C	Detector Standard, Windowless Photodiode (5 nm to 122 nm)	4012
40511C	Recalibration of Detector Standard (5 nm to 122 nm)	3626
40520C	Detector Standard, Windowless Photodiode (18 nm to 122 nm)	2860
40521C	Recalibration of Detector Standard (18 nm to 122 nm)	2474
40530C	Detector Standard, Windowless Photodiode (52 nm to 122 nm)	1708
40531C	Recalibration of Detector Standard (52 nm to 122 nm)	1322
40540C	Uncalibrated Windowless Photodiode	735
40560C	Detector Standard, Windowless Photodiode (116 nm to 254 nm)	12341
40561C	Recalibration of Detector Standard (116 nm to 254 nm)	1322
40599S	Special Tests on Detectors from the Ultraviolet (254 nm) to the Soft X-Ray Region (5 nm)	At Cost

*Fees are subject to change without notice.*

## F. Laser and Optoelectronic Components Used with Lasers

<b><u>Technical Contacts:</u></b>	<b><u>Telephone:</u></b>	<b><u>Email:</u></b>	<b><u>Mailing Address:</u></b>
John H. Lehman (CW Laser Radiometry)	(303) 497-3654	lehman@boulder.nist.gov	NIST 325 Broadway, MC 815.01
Paul D. Hale (High Speed Measurements)	(303) 497-5367	hale@boulder.nist.gov	Boulder, CO 80305-3328
Christopher L. Cromer (Pulsed-Laser Radiometry)	(303) 497-5620	cromer@boulder.nist.gov	
Timothy Drapela (Optical Fiber and Component Measurements [other than Fiber Power])	(303) 497-5858	drapela@boulder.nist.gov	

### **Administrative and Logistics:**

John Lomax (303) 497-4285 john.lomax@boulder.nist.gov  
**FAX:** (303) 497-4286

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
42110C	Laser Power and Energy Meter (or Detector) Calibrations at a Single Standard Wavelength and Power (See Table 4)	
	CW Laser Power below 2 Watts	3621
	Pulsed Laser Energy (Q-switched YAG) at 1064 nm	3663
	CW Laser Power at 1064 nm above 2 Watts and 10.6 $\mu$ m	4579
	Pulsed Laser Energy (Excimer) at 248 nm and 193 nm	4150
42111C	Same as 42110C, Additional Standard Wavelengths or Powers (See Table 4)	
	CW Laser Power below 2 Watts	1810
	Pulsed Laser Energy (Q-switched YAG) at 1064 nm	2747
	CW Laser Power at 1064 nm above 2 Watts and 10.6 $\mu$ m above 1 Watt	3663
	Pulsed Laser Energy (Excimer) at 248 nm and 193 nm	3151
42120M	Laser Power and Energy Measurement Assurance Program (MAP)	At Cost
42130C	Optical Fiber Power Meter (or Detectors Used with Lasers) Calibrations at a Single Standard Wavelength and Connector Type (See Table 5)	2632
42131C	Same as 42130C, Additional Standard Wavelengths or Connector Types (See Table 5)	1053
42140M	Optical Fiber Power Meter Measurement Assurance Program (MAP)	At Cost
42150M	Low-Level Laser Measurement Assurance Program (MAP)	At Cost
42151C	Low-Level Laser Radiometer Calibration	At Cost
42155C	Calibration Service of Optoelectronic Frequency Response for Combined Photodiode/RF Power Sensor Transfer Standards	At Cost
42160S	Special Test for Frequency Response Measurements of Detectors Used with Lasers	At Cost

42161S	Special Test for Impulse Response Measurements of Detectors Used with Lasers	At Cost
42162S	Special Test for High Accuracy Laser and Optical Fiber Power Measurements	At Cost
42164C	Spectral Responsivity Measurements of Laser and Optical Fiber Power Meters (or Detectors Used with Lasers)	2916
42165S	Special Test for Spatial Uniformity of Laser and Optical Fiber Power Meters and Detectors Used with Lasers	At Cost
42166C	Calibration for Linearity Measurements of Optical Fiber Power Meters (or Detectors Used with Lasers)	At Cost
42167S	Special Test for Linearity Measurements of High-Power Laser Power Meters (or Detectors Used with Lasers)	At Cost
42170S	Special Test for General Laser Measurements, by Prearrangement	At Cost
42180S	Special Test for General Optical Fiber Power Measurements, by Prearrangement	At Cost
42190S	Special Test for Optical Fiber and Fiber Component Measurements (other than Fiber Power) by Prearrangement	At Cost
42210C	Spectral Responsivity Measurements with Curve Fitting of Laser and Optical Meters (or Detectors used with Lasers)	3640

*Fees are subject to change without notice.*

## CHAPTER 8

### IONIZING RADIATION MEASUREMENTS

#### A. Radioactivity Sources

<b><u>Technical Contacts:</u></b> Lisa R. Karam (All Services) M.P. Unterweger (43030C, 43040C, 43070S, 43090S) Jeffrey T. Cessna (43010C, 43020C, 43060C, 43070S) Lynne King (43030C, 43040C, 43070S, 43090S)	<b><u>Telephone:</u></b> (301) 975-5561 (301) 975-5536 (301) 975-5539 (301) 975-5544	<b><u>Email:</u></b> lisa.karam@nist.gov munterweger@nist.gov jcessna@nist.gov lynne.king@nist.gov	<b><u>Mailing Address:</u></b> NIST 100 Bureau Drive, Stop 8462 Gaithersburg, MD 20899-8462 Attn: Jeffrey Cessna
---	--	--	--

**Administrative and Logistics:**

Jeffrey Cessna (301) 975-5539 jcessna@nist.gov

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
43010C	Gamma-Ray-Emitting Radionuclides in Solution (Half Lives Greater than 15 Days)	2376
43020C	Gamma-Ray-Emitting Radionuclides in Solution (Half Lives Less than 15 Days)	3939
43030C	Alpha-Particle-Emitting Solid Sources, NIST 2 $\pi$ Proportional Counter	1708
43040C	Alpha-Particle-Emitting Solid Sources, NIST 0.8 $\pi$ Defined-Solid-Angle Counter	1685
43050C	Alpha-Particle-Emitting Solid Sources, Using Both Counting Systems	3227
43060S	Special Tests of Beta-Particle-Emitting Solution Sources, Liquid Scintillation Counting	4799
43070S	Special Tests of Beta-Particle-Emitting Solution Sources, Other Techniques	At Cost
43090S	Special Tests of Alpha-Particle-Emitting Solid Sources	At Cost

*Fees are subject to change without notice.*

## B. Neutron Sources and Neutron Dosimetry

<b><u>Technical Contacts:</u></b>	<b><u>Telephone:</u></b>	<b><u>Email:</u></b>	<b><u>Mailing Address:</u></b>
M. Scott Dewey (All Services Except 44060C)	(301) 975-4843	mdewey@nist.gov	NIST 100 Bureau Drive, Stop 8461 Gaithersburg, MD 20899-8461
Alan K. Thompson (44060C, 44100S)	(301) 975-4666	alan.thompson@nist.gov	

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
44010C	Radioactive Neutron Sources Emission Rates ( $10^{-5} \text{ s}^{-1}$ to $10^{-9} \text{ s}^{-1}$ )	5169
44020C	Radioactive Neutron Sources Emission Rates ( $10^{-8} \text{ s}^{-1}$ to $10^{-10} \text{ s}^{-1}$ )	5169
44060C	Personnel Protection Instrumentation, Californium Source Bare and Moderated	At Cost
44070C	Activation Detector Dosimetry, Thermal Neutrons	At Cost
44080C	Activation Detector Dosimetry, Californium Fission Neutrons	At Cost
44090C	Activation Detector Dosimetry, $^{235}\text{U}$ Cavity Fission Sources	At Cost
44100S	Special Test of Neutron Sources and Dosimeters	At Cost

*Fees are subject to change without notice.*

## C. Dosimetry of X-Rays, Gamma-Rays, and Electrons

<b><u>Technical Contacts:</u></b>	<b><u>Telephone:</u></b>	<b><u>Email:</u></b>	<b><u>Mailing Address:</u></b>
Stephen M. Seltzer (All Services)	(301) 975-5552	s.seltzer@nist.gov	NIST
Michael Mitch (46010C-47040S)	(301) 975-5491	mmitch@nist.gov	100 Bureau Drive, Stop 8460 Gaithersburg, MD 20899-8460
Michelle O'Brien (46010C-46050S)	(301) 975-2014	michelle.obrien@nist.gov	<b>Fax:</b> (301) 869-7682
Ronaldo Minniti (46010C-46110C)	(301) 975-5586	ronaldo.minniti@nist.gov	
Heather Chen-Mayer (46110C)	(301) 975-5595	heather.chen-mayer@nist.gov	
Christopher G. Soares (47030C-47040S)	(301) 975-5589	csoares@nist.gov	

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

C.1 X-Ray and Gamma-Ray Measuring Instruments		
Service ID Number	Description of Services	Fee (\$)
<b>Air-Kerma (Exposure)</b>		
46010C	Radiation Detectors—Calibration in $^{60}\text{Co}$ and $^{137}\text{Cs}$ Gamma-Ray Beams	1785
46011C	Radiation Detectors—Calibration in X-Ray Beams (see Tables 6, 7 and 8)	1451
46020C	Passive Dosimeters—Irradiation of Up to Six, One Beam Quality at One Set-up	1803
46021C	Up to Six Additional Dosimeters at Same Set-up and Beam Quality	1146

46030S	Special Tests of High-Gain Electrometers—Charge Sensitivity, One Set of Switch Positions, with 46010C/46011C, by Prearrangement	1188
46040S	Special Tests of kV Measuring Devices	At Cost
46050S	Special Tests of X-Ray and Gamma-Ray Measuring Instruments	At Cost
<b>Absorbed Dose to Water From <sup>60</sup>Co Beam</b>		
46110C	Radiation Detectors—Calibration in a <sup>60</sup> Co Gamma-Ray Beam	2079
<b>C.2 Sealed Gamma-Ray Sources or Beta-Particle Sources, and Measuring Instruments</b>		
47010C	Gamma-Ray Sources Similar to NIST Standards— <sup>60</sup> Co to <sup>137</sup> Cs, Having Air-Kerma Strengths 10 $\mu\text{Gy m}^2/\text{h}$ to 1500 $\mu\text{Gy m}^2/\text{h}$ ; and <sup>192</sup> Ir Sources of the Same Type Used to Calibrate Reentrant Chamber, Having Air-Kerma Strengths 0.1 $\mu\text{Gy m}^2/\text{h}$ to 30 $\mu\text{Gy m}^2/\text{h}$	3279
47011C	Each Additional Gamma-Ray Source of Same Radionuclide	3169
47020C	<sup>125</sup> I or <sup>103</sup> Pd Sources: Seeds Having Air-Kerma Strengths 0.5 $\mu\text{Gy m}^2/\text{h}$ to 100 $\mu\text{Gy m}^2/\text{h}$	3249
47021C	Each Additional <sup>125</sup> I or <sup>103</sup> Pd Source of Same Radionuclide/Design Submitted with Above	3179
47030C	Beta-Particle Source Calibrated for Surface Dose Rate	2161
47035C	Beta-Particle Source Calibrated for Radiation Protection	1751
47036C	Ionization Chamber Calibrated with Beta-Particle Sources for Radiation Protection	1751
47040S	Special Tests of Gamma-Ray and Beta-Particle Sources	At Cost

*Fees are subject to change without notice.*

#### **D. Dosimetry for High-Dose Applications**

**Technical Contacts:**

Stephen M. Seltzer  
 Marc D. Desrosiers  
 James M. Puhl  
 Sarenee L. Cooper

**Telephone:**

(301) 975-5552  
 (301) 975-5639  
 (301) 975-5581  
 (301) 975-5054

**Email:**

s.seltzer@nist.gov  
 mdesrosiers@nist.gov  
 jpuhl@nist.gov  
 sarenee.cooper@nist.gov

**Mailing Address:**

NIST  
 100 Bureau Drive, Stop 8460  
 Gaithersburg, MD 20899-8460

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
<b>D.1 Dosimetry of High-Energy Electron Beams</b>		
48010M	Dose Interpretation of NIST-Packaged Dosimeters Irradiated by Customer—Two Dosimeters	981
48011M	Each Additional Dosimeter	521
48020S	Special Tests of Electron-Beam Dosimeters	At Cost



<b>D.2 Dosimetry of Photon Beams</b>		
49010C	Calibration Irradiations of Customer Supplied Dosimeters with $^{60}\text{Co}$ Gamma-Rays	913
49020C	Dose Interpretation of NIST Transfer Dosimeters Irradiated by Customer, Three Dosimeters Plus Control(s)	2607
49030C	Dose Interpretation of Each NIST Transfer Dosimeter Package in Addition to Those Supplied Under 49020C	675
49050S	Special Measurement Services for Dosimeter Response and Dose Distributions	At Cost

*Fees are subject to change without notice.*

## CHAPTER 9

### ELECTROMAGNETIC MEASUREMENTS

#### A. Resistance Measurements

##### A.1 DC Resistance Standards and Measurements

<b><u>Technical Contacts:</u></b>	<b><u>Telephone:</u></b>	<b><u>Email:</u></b>	<b><u>Mailing Address:</u></b>
George R. Jones	(301) 975-4225	george.jones@nist.gov	NIST
Randolph E. Elmquist	(301) 975-6591	relmquist@nist.gov	100 Bureau Drive, Stop 8170 Gaithersburg, MD 20899-8170

**Administrative and Logistics:**  
Denise D. Prather (301) 975-4221 dprather@nist.gov

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
51100S	Special Resistance Measurements Services, by Prearrangement	At Cost
51110M	Measurement Assurance Program for Resistance	At Cost
51130C	Standard Resistor, Thomas-Type, 1 $\Omega$	1784
51131C	Standard Resistor, Evanohm Wirewound High Precision, 10 k $\Omega$	1718
51132C	Standard Resistor, Four-Terminal 0.0001 $\Omega$	2091
51133C	Standard Resistor, Four-Terminal 0.001 $\Omega$	1796
51134C	Standard Resistor, Four-Terminal 0.01 $\Omega$	1796
51135C	Standard Resistor, Four-Terminal 0.1 $\Omega$	1353
51136C	Standard Resistor, Four-Terminal 1 $\Omega$	1353
51137C	Standard Resistor, Four-Terminal 10 $\Omega$	1353
51138C	Standard Resistor, Four-Terminal 100 $\Omega$	1353
51139C	Standard Resistor, 1 k $\Omega$	1353
51140C	Standard Resistor, 10 k $\Omega$	1737
51141C	Standard Resistor, 100 k $\Omega$	1737
51142C	Standard Resistor, 1 M $\Omega$	1927
51143C	Standard Resistor, 10 M $\Omega$	2147
51144C	Additional Voltage, 10 M $\Omega$	1761
51145C	Standard Resistor, 100 M $\Omega$	2147
51146C	Additional Voltage, 100 M $\Omega$	1761
51147C	Standard Resistor, 1 G $\Omega$	2147
51148C	Additional Voltage, 1 G $\Omega$	1761

51149C	Standard Resistor, 10 GΩ	2736
51150C	Additional Voltage, 10 GΩ	2350
51151C	Standard Resistor, 100 GΩ	2736
51152C	Additional Voltage, 100 GΩ	2350
51153C	Standard Resistor, 1 TΩ	2883
51154C	Additional Voltage, 1 TΩ	2792
51160C	Standard Resistor for Current Measurements (Shunts) with all determinations at 300 A or Below, One Range, One Current Level	2689
51161C	Standard Resistor for Current Measurements (Shunts), with At Least One Determination Above 300 A (maximum current 2000 A), One Range, One Current Level	3629
51162C	Standard Resistor for Current Measurements (Shunts), Additional Range of a Multi-Range Resistor	1649
51163C	Standard Resistor for Current Measurements (Shunts), Additional Determination at Another Current Level	1649

*Fees are subject to change without notice.*

## **A.2 High-Voltage Standard Resistors**

### **Technical Contacts:**

Gerald J. FitzPatrick

### **Telephone:**

(301) 975-8922

### **Email:**

gfitzpatrick@nist.gov

### **Mailing Address:**

NIST  
100 Bureau Drive, Stop 8170  
Gaithersburg, MD 20899-8170

### **Administrative and Logistics:**

Denise D. Prather

(301) 975-4221 dprather@nist.gov

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
51210C	High-Voltage Standard Resistors	At Cost

### A.3 High-Frequency Standard Resistors

**Technical Contact:**

Ronald A. Ginley

**Telephone:**

(303) 497-3634

**Email:**

rginley@boulder.nist.gov

**Mailing Address:**

NIST  
325 Broadway, MC 818.01  
Boulder, CO 80305-3328

**Administrative and Logistics:**

Puanani L. DeLara

(303) 497-3753 calibration@boulder.nist.gov

**Fax:** (303) 497-3970

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
51310S	High-Frequency Standard Resistors; Two-Terminal	At Cost

### B. Impedance Measurements (Except Resistors)

#### B.1 Low-Frequency Capacitance and Inductance Measurements and Standards

**Technical Contacts:**

Andrew D. Koffman

**Telephone:**

(301) 975-4518

**Email:**

akoffman@nist.gov

**Mailing Address:**

NIST  
100 Bureau Drive, Stop 8170  
Gaithersburg, MD 20899-8170

**Administrative and Logistics:**

Denise D. Prather

(301) 975-4221 dprather@nist.gov

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
52100S	Special Four Terminal-Pair (4TP) Capacitance and Dissipation Factor Characterization	At Cost
52110S	Special LF Capacitance Measurements, by Prearrangements	At Cost
52120S	Special Measurement Assurance Program for Standard Capacitors (100 pF and 1000 pF, at a Frequency of 1000 Hz)	At Cost
52130C	Fixed, Fused-Silica Dielectric Standard Capacitors (1, 10, and 100) pF, at a Frequency of (100, 400, or 1000) Hz	2895
52131C	Additional Measurement at One of the Above Frequencies	304
52140C	Fixed Three-Terminal, High-Precision Nitrogen Dielectric Standard Capacitors with Coaxial Connectors, Small Uncertainty, (10, 100 and 1000) pF, at a Frequency of (100, 400, or 1000) Hz	1840
52141C	Additional Measurement at One of the Above Frequencies	291
52150C	Physical Tests for Three-Terminal Standard Capacitors with Coaxial Connectors, Large Uncertainty (0.001 pF to 10 000 pF) at a Frequency of (100, 400, or 1000) Hz	1804
52160C	Fixed Three-Terminal Standard Capacitors with Coaxial Connectors, Large Uncertainty (0.001 pF to 10 000 pF) at a Frequency of (100, 400, or 1000) Hz	1211

52161C	Additional Measurement at One of the Above Frequencies	291
52170C	Two- or Three- Terminal Mica Dielectric Standard Capacitors with Binding Post Connectors (0.001 $\mu$ F to 1 $\mu$ F), at a Frequency of (66, 100, 400, 1000 or 10 000) Hz	1211
52171C	Additional Measurement at One of the Above Frequencies	291
52176C	Two-Terminal Standard Capacitors with Precision High Frequency (HF) Coaxial Connectors (0.001 pF to 10 000 pF), at a Frequency of 1000 Hz	At Cost
52180C	Fixed Standard Inductors (0.00005 H to 10 H), at a Frequency of (100, 400, 1000, or 10 000) Hz	1211
52181C	Additional Measurement at One of the Above Frequencies	1151
52190S	Special LF Inductance Measurements, by Prearrangement	At Cost

*Fees are subject to change without notice.*

## B.2 High-Frequency Standard Capacitors and Inductors

**Technical Contact:**

Ronald A. Ginley

**Telephone:**

(303) 497-3634

**Email:**

rginley@boulder.nist.gov

**Mailing Address:**

NIST  
325 Broadway, MC 818.01  
Boulder, CO 80305-3328

**Administrative and Logistics:**

Puanani L. DeLara (303) 497-3753 calibration@boulder.nist.gov

**Fax:** (303) 497-3970

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
52210S	Two-Terminal Low-Loss Standard Capacitors—10 kHz to 250 MHz; 1 pF to 20 pF	At Cost
52211S	Two-Terminal Low-Loss Standard Capacitors (High Accuracy)—10 kHz to 30 MHz, (50, 100, 200, 500 and 1000) pF	At Cost
52221C	Three-Terminal Low-Loss Standard Capacitors (High Accuracy)—10 kHz to 10 MHz, ( $10^{-2}$ , $10^{-1}$ , 1, 10, $10^2$ and $10^3$ ) pF	At Cost
52310S	Two-Terminal, High- $Q$ Standard Inductors ( $10^{-2}$ $\mu$ H to 1 H)	At Cost

*Fees are subject to change without notice.*

### B.3 Power-Frequency Capacitors

**Technical Contacts:**

Gerald J. FitzPatrick

**Telephone:**

(301) 975-8922

**Email:**

gfitzpatrick@nist.gov

**Mailing Address:**

NIST

100 Bureau Drive, Stop 8170

Gaithersburg, MD 20899-8170

**Administrative and Logistics:**

Denise D. Prather

(301) 975-4221 dprather@nist.gov

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
52400C	Power-Frequency Capacitors	At Cost

### B.4 Q-Standards

**Technical Contact:**

Ronald A. Ginley

**Telephone:**

(303) 497-3634

**Email:**

rginley@boulder.nist.gov

**Mailing Address:**

NIST

325 Broadway, MC 818.01

Boulder, CO 80305-3328

**Administrative and Logistics:**

Puanani L. DeLara

(303) 497-3753 calibration@boulder.nist.gov

**Fax:** (303) 497-3970

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
52710C	Inductive <i>Q</i> -Standards; 50 kHz to 45 MHz, 0.25 $\mu$ H to 25 mH	At Cost
52711C	Each Additional Frequency for 52710C	At Cost

*Fees are subject to change without notice.*

## C. Voltage Measurements

### C.1 DC Voltage Measurements and Standards

**Technical Contacts:**

June E. Sims

Yi-hua Tang

**Telephone:**

(301) 975-4238

(301) 975-4691

**Email:**

june.sims@nist.gov

ytang@nist.gov

**Mailing Address:**

NIST

100 Bureau Drive, Stop 8170  
Gaithersburg, MD 20899-8170

**Administrative and Logistics:**

Denise D. Prather

(301) 975-4221 dprather@nist.gov

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
53110S	Special DC Voltage Measurements, by Prearrangement	At Cost
53130C	First Saturated Standard Cell in a Group	1984
53131C	Each Additional Cell	1338
53140C	Platinum Resistance Thermometer Temperature Determination for Standard Cell Calibration	472
53150C	Unsaturated Standard Cells	1131
53160C	Tests of Solid-State Voltage Reference Standard (1 Output, 1 V to 10 V)	1770
53161C	Each Additional Output	1123
53180S	Special Handling (Equipment Pickup or Delivery)	216
53190S	Special Handling (Cleaning, Minor Repair, Return Service Charge)	435

*Fees are subject to change without notice.*

### C.2 AC Voltage Measurements

**Technical Contacts:**

Mark E. Parker

Bryan C. Waltrip

**Telephone:**

(301) 975-2413

(301) 975-2438

**Email:**

mparker@nist.gov

bwaltrip@nist.gov

**Mailing Address:**

NIST

100 Bureau Drive, Stop 8170  
Gaithersburg, MD 20899-8170

**Administrative and Logistics:**

Denise D. Prather

(301) 975-4221 dprather@nist.gov

Service ID Number	Description of Services	Fee (\$)
53200S	Special Tests of High-Accuracy Digital Multimeters, Multifunction Calibrators, by Prearrangement	At Cost
53201S	Special Tests of Low-Voltage AC-DC Transfer Standards, by Prearrangement	At Cost
53202S	Special 25-Point Test of Digital Multimeters (DMMs), by Prearrangement	1600
53203S	Each Additional DMM Test Point for 53202S	At Cost

*Fees are subject to change without notice.*

### C.3 AC-DC Thermal Voltage and Current Converters (to 1 MHz)

**Technical Contacts:**

Joseph R. Kinard  
Thomas E. Lipe

**Telephone:**

(301) 975-4250  
(301) 975-4251

**Email:**

jkinard@nist.gov  
tlpe@nist.gov

**Mailing Address:**

NIST  
Building 220, Room B146  
100 Bureau Drive, Stop 8170  
Gaithersburg, MD 20899-8170

**Administrative and Logistics:**

Denise D. Prather

(301) 975-4221 dprather@nist.gov

Service ID Number	Description of Services	Fee (\$)
53310S	Special AC-DC Measurement Services, by Prearrangement	At Cost
53350C	Set-up Charge (No Test Points Included) for a Standard or Standards Set for AC-DC Difference (Voltage or Current)	1713
53351C	First Point for Each Applied Voltage or Current Range	792
53352C	Additional Points for Each Applied Voltage and Current Level (Additional Frequency/Voltage or Frequency/Current Points)	57

*Fees are subject to change without notice.*

### D. Precision Ratio Measurements

#### D.1 Inductive Dividers

**Technical Contact:**

Scott Shields

**Telephone:**

(301) 975-4232

**Email:**

scott.shields@nist.gov

**Mailing Address:**

NIST  
100 Bureau Drive, Stop 8170  
Gaithersburg, MD 20899-8170

**Administrative and Logistics:**

Denise D. Prather

(301) 975-4221 dprather@nist.gov

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
54110S	Special Ratio Measurements and Tests of Inductive Voltage Dividers, by Prearrangement	At Cost
54120C	Inductive Voltage Dividers – (Single Frequency, Voltage to be Specified, Each Setting of 3 Most Significant Dials)	3891
54121C	Additional Frequency Points	3891
54130C	Inductive Voltage Dividers – (Single Frequency, Voltage to be Specified, Each Setting of Most Significant Dial Only)	2457
54131C	Additional Frequency Points	2457

*Fees are subject to change without notice.*



## D.2 Resistive Dividers

**Technical Contacts:**

Gerald J. FitzPatrick

**Telephone:**

(301) 975-8922

**Email:**

gfitzpatrick@nist.gov

**Mailing Address:**

NIST

100 Bureau Drive, Stop 8170

Gaithersburg, MD 20899-8170

**Administrative and Logistics:**

Denise D. Prather

(301) 975-4221 dprather@nist.gov

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
54210C	Resistor and Resistive Dividers, Total Resistance or Voltage Ratio, Two Direct Voltage Levels Between 10 kV and 150 kV	2972
54211S	Special Tests of Resistor and Resistive Dividers at Direct Voltage Levels, by Prearrangement	At Cost
54213S	Special Tests of Resistor and Resistive Dividers at 60 Hz, by Prearrangement	At Cost

*Fees are subject to change without notice.*

## D.3 Capacitive Dividers

**Technical Contacts:**

Gerald J. FitzPatrick

**Telephone:**

(301) 975-8922

**Email:**

gfitzpatrick@nist.gov

**Mailing Address:**

NIST

100 Bureau Drive, Stop 8170

Gaithersburg, MD 20899-8170

**Administrative and Logistics:**

Denise D. Prather

(301) 975-4221 dprather@nist.gov

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
54310S	Special Test of Capacitive Dividers at 60-Hz, by Prearrangement	At Cost

#### D.4 Voltage and Current Transformers

**Technical Contacts:**

Gerald J. FitzPatrick  
Thomas L. Nelson

**Telephone:**

(301) 975-8922  
(301) 975-2986

**Email:**

gfitzpatrick@nist.gov  
tnelson@nist.gov

**Mailing Address:**

NIST  
100 Bureau Drive, Stop 8170  
Gaithersburg, MD 20899-8170

**Administrative and Logistics:**

Denise D. Prather

(301) 975-4221 dprather@nist.gov

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
54510C	Voltage Transformer, Ratio & Phase Angle, at 60 Hz on 1 Range, 1 Secondary Voltage, 1 Burden Primary Vrms $\leq$ 150 kV	At Cost
54520C	Current Transformer, Ratio & Phase Angle, 1 Range at 1 Frequency, 1 Burden, Secondary Currents (0.5, 1, 2, 3, 4, 5) A, Primary Current Not Over 12 000 A	3669
54521C	Current Transformer, Ratio & Phase Angle, 1 Secondary Current, Additional Combination of Range, Frequency, and Burden, Primary Current Not Over 12 000 A	363
54522C	Current Transformer, Ratio & Phase at Each Additional Secondary Current, Same Combination of Range, Frequency, and Burden as 54520C or 54521C	291
54600S	Special Tests of Dividers and Transformers, by Prearrangement	At Cost

*Fees are subject to change without notice.*

#### E. Phase Meters and Standards and VOR Measurements

**Technical Contacts:**

Mark E. Parker  
Bryan C. Waltrip

**Telephone:**

(301) 975-2413  
(301) 975-2438

**Email:**

mparker@nist.gov  
bwaltrip@nist.gov

**Mailing Address:**

NIST  
100 Bureau Drive, Stop 8170  
Gaithersburg, MD 20899-8170

**Administrative and Logistics:**

Denise D. Prather

(301) 975-4221 dprather@nist.gov

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
55110S	Special Tests of Phase Standards and Related Instruments, by Prearrangement	At Cost
55120C	Phase Meters – One Combination of Input Voltages (0.5 V to 120 V) at One Frequency (2 Hz to 100 kHz) – the Input Voltage Ratio Shall Not Exceed 10	1384
55121C	Phase Meters – Each Additional Combination of Input Voltages (0.5 V to 120 V) at the Same or at a Different Frequency (2 Hz to 100 kHz) – the Input Voltage Ratio Shall Not Exceed 10	451
55130C	Phase Meters – One Additional Combination of One Input Voltage (0.5 V to 120 V) and One Input Current (1 A to 5 A) at One Frequency (2 Hz to 4 kHz)	1796
55131C	Phase Meters – Each Additional Combination of One Input Voltage (0.5 V to 120 V) and One Input Current (0.5 A to 5 A)	510

55140C	Phase Meters – One Input Voltage (120 V to 240 V) and Another Input Voltage (120 V to 240 V) at One Frequency (2 Hz to 5 kHz)	1796
55141C	Phase Meters – Each Additional Combination of One Input Voltage (120 V to 240 V) and Another Input Voltage (120 V to 240 V) at the Same or at a Different Frequency (2 Hz to 5 kHz)	510

*Fees are subject to change without notice.*

#### **F. Power and Energy Measurements, Low-Frequency**

**Technical Contacts:**

Thomas L. Nelson  
Gerald J. FitzPatrick

**Telephone:**

(301) 975-2986  
(301) 975-8922

**Email:**

tnelson@nist.gov  
gfitzpatrick@nist.gov

**Mailing Address:**

NIST  
100 Bureau Drive, Stop 8170  
Gaithersburg, MD 20899-8170

**Administrative and Logistics:**

Denise D. Prather (301) 975-4221 dprather@nist.gov

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
56110S	Special Test of AC-DC Wattmeters, by Prearrangement	At Cost
56200C	Watt, Watthour, Var, Varhour Meter, Initial Two Determinations of Same Meter at 60 Hz	3332
56201C	Each Additional Determination, Same Meter at 50 Hz	206
56202C	Initial Two Determinations of One or Two Meters Run Simultaneously with the First (56200C)	3018
56210M	Measurement Assurance Program for Watthour Meters	4310
56220S	Special Tests of Watthour Meter with Pulse Output; 120 Volts, 5 Amperes, 60 Hz at 0.5 Lag, Unity and 0.5 Lead Power Factors	1407

*Fees are subject to change without notice.*

## G. RF, Microwave and Millimeter-Wave Measurements

### G.1 Thermistor Detectors

**Technical Contacts:**

Ronald A. Ginley  
Thomas P. Crowley

**Telephone:**

(303) 497-3634  
(303) 497-4133

**Email:**

rginley@boulder.nist.gov  
crowley@boulder.nist.gov

**Mailing Address:**

NIST  
325 Broadway, MC 818.01  
Boulder, CO 80305-3328

**Administrative and Logistics:**

Puanani L. DeLara

(303) 497-3753 calibration@boulder.nist.gov

**Fax:** (303) 497-3970

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
<b>The following tests are for 50 <math>\Omega</math> thermistor and thermoelectric detectors with coaxial connectors.</b>		
61100S	Measurement setup charge (applies to all coaxial power measurements—one setup charge for multiple detectors with the same connectors and frequencies <sup>1</sup> )	1954
61110S	Coaxial Detectors in the Frequency Range from 0.1 MHz to 10 MHz	2333
61120S	Coaxial Detectors at user Selected Frequencies in the appropriate Frequency Range for the Connector Type <sup>2</sup> . Up to 20 Frequency Points	2541
61121S	Coaxial Detectors at user Selected Frequencies in the appropriate Frequency Range for the Connector Type <sup>2</sup> . 20 to 40 Frequency Points	2801
61122S	Coaxial Detectors at user Selected Frequencies in the appropriate Frequency Range for the Connector Type <sup>2</sup> . 40 to 120 Frequency Points	3060
61123S	Coaxial Detectors at user Selected Frequencies in the appropriate Frequency Range for the Connector Type <sup>2</sup> . More than 120 Frequency Points	3579
61137C	NIST Model CN Coaxial Detectors at 21 Frequencies within the Frequency Range of 50 MHz to 18 GHz	6393
61138C	NIST Model CN Coaxial Detectors at Single Customer Selected Frequency within the Frequency Range of 50 MHz to 18 GHz	45
<b>The following tests are for thermistor detectors with waveguide flanges.</b>		
61140S	Measurement setup charge (applies to all waveguide power measurements EXCEPT WR15—one charge for multiple detectors with the same connectors and frequencies <sup>1</sup> )	3807
61141S	Measurement setup charge (applies to all WR15 waveguide power measurements—one charge for multiple detectors with the same connectors and frequencies <sup>1</sup> )	2843
61142S	Rectangular Waveguide Detectors with WR90 Flanges <sup>2</sup>	2607
61143S	Rectangular Waveguide Detectors with WR62 Flanges <sup>2</sup>	2607
61144S	Rectangular Waveguide Detectors with WR42 Flanges <sup>2</sup>	2607
61145S	Rectangular Waveguide Detectors with WR28 Flanges <sup>2</sup>	2739

61146S	Rectangular Waveguide Detectors with WR22 Flanges <sup>2</sup>	3035
61147S	Rectangular Waveguide Detectors with WR15 Flanges <sup>2</sup>	4809
61148S	Rectangular Waveguide Detectors with WR10 Flanges <sup>2</sup>	5570
<b>Miscellaneous Tests</b>		
61190S	Special Microwave and RF Power Measurement Services, by Prearrangement	At Cost
<sup>1</sup> Only one setup charge is necessary for multiple detectors sent in at the same time with the same connector type and measurement frequencies.		
<sup>2</sup> Measurement Frequencies		

*Fees are subject to change without notice.*

## G.2 Scattering Parameters of Passive One and Two-Port Devices

### **Technical Contacts:**

Ronald A. Ginley

### **Telephone:**

(303) 497-3634

### **Email:**

rginley@boulder.nist.gov

### **Mailing Address:**

NIST  
325 Broadway, MC 818.01  
Boulder, CO 80305-3328

### **Administrative and Logistics:**

Puanani L. DeLara

(303) 497-3753 calibration@boulder.nist.gov

**Fax:** (303) 497-3970

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
<b>The following tests are for two-port 50 <math>\Omega</math> devices with coaxial connectors</b>		
61200S	Measurement setup charge for all Coaxial Two-port measurements with GR900, GC7 or Type-N connectors, frequencies of 0.05 GHz and 0.1 GHz—one setup charge for multiple devices with the same connectors and frequencies <sup>1</sup>	455
61201S	Measurement setup charge for all Coaxial Two-port measurements with GR900, GC7 or Type-N connectors, frequencies at or above 0.2 GHz—one setup charge for multiple devices with the same connectors and frequencies <sup>1</sup>	2103
61202C	Measurement setup charge for all Coaxial Two-port measurements with 3.5 mm, 2.92 mm, or 2.4 mm connectors and frequencies of 0.05 GHz and 0.1 GHz—one setup charge for multiple devices with the same connectors and frequencies <sup>1</sup>	455
61203S	Measurement setup charge for all Coaxial Two-port measurements with 3.5 mm, 2.92 mm, or 2.4 mm connectors and frequencies at or above 0.2 GHz—one setup charge for multiple devices with the same connectors and frequencies <sup>1</sup>	2755
61211S	Fixed Two-port Devices with GR900, GPC7 or Type-N connectors <sup>2</sup>	3227
61212S	Variable Two-port Devices with GR900, GPC7 or Type-N connectors <sup>2</sup>	3227
61213S	Fixed Two-port Devices with 3.5 mm, 2.92 mm, or 2.4 mm connectors <sup>2</sup>	2455
61214S	Variable Two-port Devices with 3.5 mm, 2.92 mm, or 2.4 mm connectors <sup>2</sup>	2567

<b>The following tests are for two-port devices with waveguide flanges.</b>		
61220S	Measurement setup charge for all Waveguide Two-port measurements EXCEPT WR15—one setup charge for multiple devices with the same connectors and frequencies <sup>1</sup>	2725
61221S	Measurement setup charge for all WR15 Waveguide Two-port measurements—one setup charge for multiple devices with the same connectors and frequencies <sup>1</sup>	3113
61222S	Additional Measurement setup charge for all VARIABLE Waveguide Two-port measurements—one setup charge for multiple devices with the same connectors and frequencies <sup>1</sup>	500
61223S	Fixed and Variable Rectangular Waveguide Two-port Devices with WR90 Flanges <sup>2</sup>	2516
61224S	Fixed and Variable Rectangular Waveguide Two-port Devices with WR62 Flanges <sup>2</sup>	2480
61225S	Fixed and Variable Rectangular Waveguide Two-port Devices with WR42 Flanges <sup>2</sup>	2592
61226S	Fixed and Variable Rectangular Waveguide Two-port Devices with WR28 Flanges <sup>2</sup>	2592
61227S	Fixed and Variable Rectangular Waveguide Two-port Devices with WR22 Flanges <sup>2</sup>	2592
61228S	Fixed and Variable Rectangular Waveguide Two-port Devices with WR15 Flanges <sup>2</sup>	5036
61231S	Fixed and Variable Rectangular Waveguide Two-port Devices with WR10 Flanges <sup>2</sup>	5148
<b>The following tests are for one-port 50 <math>\Omega</math> devices with coaxial connectors</b>		
61250S	Measurement setup charge for all Coaxial One-port measurements with GR900, GC7 or Type-N connectors, frequencies of 0.05 GHz and 0.1 GHz—one setup charge for multiple devices with the same connectors and frequencies <sup>1</sup>	605
61251S	Measurement setup charge for all Coaxial One-port measurements with GR900, GC7 or Type-N connectors, frequencies at or above 0.2 GHz—one setup charge for multiple devices with the same connectors and frequencies <sup>1</sup>	2177
61252S	Measurement setup charge for all Coaxial One-port measurements with 3.5 mm, 2.92 mm, or 2.4 mm connectors and frequencies of 0.05 GHz and 0.1 GHz—one setup charge for multiple devices with the same connectors and frequencies <sup>1</sup>	566
61253S	Measurement setup charge for all Coaxial One-port measurements with 3.5 mm, 2.92 mm, or 2.4 mm connectors and frequencies at or above 0.2 GHz—one setup charge for multiple devices with the same connectors and frequencies <sup>1</sup>	2787
61261S	Fixed One-port Devices with GR900, GPC7 or Type-N connectors <sup>2</sup>	2812
61262S	Variable One-port Devices with GR900, GPC7 or Type-N connectors <sup>2</sup>	2812
61263S	Fixed One-port Devices with 3.5 mm, 2.92 mm, or 2.4 mm connectors <sup>2</sup>	2293
61264S	Variable One-port Devices with 3.5 mm, 2.92 mm, or 2.4 mm connectors <sup>2</sup>	2516

<b>The following tests are for one-port devices with waveguide flanges.</b>		
61270S	Measurement setup charge for all Waveguide One-port measurements —one setup charge for multiple devices with the same connectors and frequencies <sup>1</sup>	2831
61271S	Additional Measurement setup charge for all VARIABLE Waveguide One-port measurements —one setup charge for multiple devices with the same connectors and frequencies <sup>1</sup>	493
61272S	Fixed and Variable Rectangular Waveguide One-port Devices with WR90 Flanges <sup>2</sup>	2293
61273S	Fixed and Variable Rectangular Waveguide One-port Devices with WR62 Flanges <sup>2</sup>	2369
61274S	Fixed and Variable Rectangular Waveguide One-port Devices with WR42 Flanges <sup>2</sup>	2369
61275S	Fixed and Variable Rectangular Waveguide One-port Devices with WR28 Flanges <sup>2</sup>	2369
61276S	Fixed and Variable Rectangular Waveguide One-port Devices with WR22 Flanges <sup>2</sup>	2369
61277S	Fixed and Variable Rectangular Waveguide One-port Devices with WR15 Flanges <sup>2</sup>	4964
61278S	Fixed and Variable Rectangular Waveguide One-port Devices with WR10 Flanges <sup>2</sup>	4964
<b>Miscellaneous Tests</b>		
61290S	Special Microwave and RF Power Measurement Services, by Prearrangement	At Cost
<sup>1</sup> Only one setup charge is necessary for multiple detectors sent in at the same time with the same connector type and measurement frequencies <sup>2</sup> Measurement Frequencies		

*Fees are subject to change without notice.*

### **G.3 High-Accuracy Attenuation Measurements**

**Technical Contacts:**

Ronald A. Ginley  
Jeff Jargon

**Telephone:**

(303) 497-3634  
(303) 497-3516

**Email:**

rginley@boulder.nist.gov  
jargon@boulder.nist.gov

**Mailing Address:**

NIST  
325 Broadway, MC 818.01  
Boulder, CO 80305-3328

**Administrative and Logistics:**

Puanani L. DeLara

(303) 497-3753 calibration@boulder.nist.gov

**Fax:** (303) 497-3970

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
61300S	High-Accuracy Attenuation: Set Up Charge, per order	At Cost

61330S	Attenuation Measurements of Three-Port and Two-Port Devices at 1.25 MHz, 0 dB and 6 dB	At Cost
61350C	Coaxial Fixed and Variable Phase Shifters; Characteristics Phase Shift Difference; Precision Connectors; Measured at 30 MHz, Range 0° to 360°	At Cost

#### G.4 Thermal Noise Measurements

**Technical Contacts:**

David Walker  
James Randa

**Telephone:**

(303) 497-5490  
(303) 497-3150

**Email:**

dwalker@boulder.nist.gov  
randa@boulder.nist.gov

**Mailing Address:**

NIST  
325 Broadway, MC 818.01  
Boulder, CO 80305-3328

**Administrative and Logistics:**

Puanani L. DeLara

(303) 497-3753 calibration@boulder.nist.gov

**Fax:** (303) 497-3970

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Freq.	Connector Type	Device Requirements/Service	Fee (\$)
61410S	30 MHz 60 MHz	<i>Coaxial</i> N Precision (PIN) GPC 3.5 (PIN) GPC 7 14 mm	Temperature < 15 000 K (ENR < 17 dB) VSWR < 1.2	
				<b>Set Up Charge, per order</b> 3141
				<b>Per Frequency</b> 5145
61420S	1.0 GHz to 12.4 GHz Continuous Frequencies	<i>Coaxial</i> 14 mm (1 to 4 GHz) GPC 7 N Precision (PIN) GPC 3.5 (PIN) GPC 2.4 (PIN) (8 to 12.4 GHz)	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
				<b>Set Up Charge, per order</b> 4337
				<b>Per Frequency</b> 505
61425S	12.4 GHz to 18.0 GHz Continuous Frequencies	<i>Coaxial</i> GPC 7 N Precision (PIN) GPC 3.5 (PIN) GPC 2.4 (PIN)	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
				<b>Set Up Charge, per order</b> 5874
				<b>Per Frequency</b> 3393



61430S	18.0 GHz to 26 GHz Continuous Frequencies	<i>Coaxial</i> GPC 3.5 (PIN) GPC 2.4 (PIN)	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
	<b>Set Up Charge, per order</b>			5727
	<b>Per Frequency</b>			3267
61435S	26.5 GHz to 40 GHz Continuous Frequencies	<i>Coaxial</i> GPC 2.4 (PIN)	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
	<b>Set Up Charge, per order</b>			8223
	<b>Per Frequency</b>			4759
61450S	8.2 GHz to 12.4 GHz Continuous Frequencies	<i>Waveguide</i> WR 90	Temperature <15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
	<b>Set Up Charge, per order</b>			4485
	<b>Per Frequency</b>			495
61455S	12.4 GHz to 18.0 GHz Continuous Frequencies	<i>Waveguide</i> WR 62	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
	<b>Set Up Charge, per order</b>			5727
	<b>Per Frequency</b>			3164
61460S	18.0 GHz to 26.0 GHz Continuous Frequencies	<i>Waveguide</i> WR 42	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
	<b>Set Up Charge, per order</b>			5727
	<b>Per Frequency</b>			3164
61465S	26.5 GHz to 40.0 GHz Continuous Frequencies	<i>Waveguide</i> WR 28	Temperature < 15 000 K (ENR < 17 dB) Reflection Coefficient < 0.2	
	<b>Set Up Charge, per order</b>			7469
	<b>Per Frequency</b>			3563
61470S	33 GHz to 50 GHz Continuous Frequencies	<i>Waveguide</i> WR 22	Temperature <15 000 K (ENR < 17 dB) Reflection Coefficient <0.2	
	<b>Set Up Charge, per order</b>			7972
	<b>Per Frequency</b>			4464

61475S	50 GHz to 65 GHz Continuous Frequencies	<i>Waveguide</i> WR 15	Temperature < 15 000 K (ENR , 17 dB) Reflection Coefficient < 0.2	
	<b>Set Up Charge, per order</b>			7972
	<b>Per Frequency</b>			5795
61495S	Special Noise Temperature Measurements, by Prearrangement			At Cost

*Fees are subject to change without notice.*

#### **G.5 Microwave Dielectric and Magnetic Material Measurements**

**Technical Contact:**

James R. Baker-Jarvis

**Telephone:**

(303) 497-5621

**Email:**

jjarvis@boulder.nist.gov

**Mailing Address:**

NIST  
325 Broadway, MC 818.01  
Boulder, CO 80305-3328

**Administrative and Logistics:**

Puanani L. DeLara

(303) 497-3753

calibration@boulder.nist.gov

**Fax:** (303) 497-3970

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
61620S	Special Tests for Dielectric and Magnetic Materials 1 kHz to 60 GHz	At Cost
61640S	Special Consulting and Advisory Services for Dielectric and Magnetic Materials, by Prearrangement	At Cost

## H.1 Microwave Antenna Parameter Measurements

**Mailing Address:**

NIST

325 Broadway, MC 818.02

Boulder, CO 80305-3328

\_\_\_\_\_

francis@boulder.nist.gov

(2002) 121-2072

## calibration@boulder.nist.gov

**Fax:** (303) 497-3970

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
63100S	Gain and Polarization Calibrations of Standard Antennas Using Extrapolation Range	At Cost
63200S	Measurement of Pattern, Gain, and Polarization of Arbitrary Antennas Using Near-Field Scanning Techniques	At Cost
63300S	Special Test Service for Calibration of Probes Used with Near-Field Scanning Facilities	At Cost
63400S	Special Consulting, Advisory, and Other Services	At Cost

**Mailing Address:**

NIST

325 Broadway, MC 818.02

Boulder, CO 80305-3328

## calibration@boulder.nist.gov

**Fax:** (303) 497-3970

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
64100S	Special Test Services for Antenna/Field Strength/M Measurement, Using the Transverse Electromagnetic (TEM) Cell Method (10 kHz to 300 MHz)	At Cost
64200S	Special Test Services for Antenna/Field Strength/Measurements, Utilizing the Open Area Test Site and Standard Antenna Method	At Cost
64300S	Special Test Services for Antenna/Field Strength/Reflectivity Measurements, Utilizing the Anechoic Chamber and Standard Field Method	At Cost

## I. Pulse Waveform Measurements

### **Technical Contacts:**

Paul Hale (65100S, 65200S and  
65400S)

### **Telephone:**

(303) 497-5367

### **Email:**

hale@boulder.nist.gov

### **Mailing Address:**

NIST  
325 Broadway, MC 815.01  
Boulder, CO 80305-3328

David I. Bergman (65250S,  
65500S and 65501S)

(301) 975-4464

dbergman@nist.gov

NIST  
100 Bureau Drive, Stop 8170  
Gaithersburg, MD 20899-8170

### **Administrative and Logistics (65100S, 65200S and 65400S):**

John Lomax

(303) 497-4285

**FAX:** (303) 497-4286

### **Administrative and Logistics (65250S, 65500S and 65501S):**

Denise D. Prather

(301) 975-4221 dprather@nist.gov

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
65100S	Impulse Spectrum Amplitude (50 $\Omega$ )	At Cost
65200S	Fast Repetitive Pulse Transition Parameters (50 $\Omega$ )	At Cost
65250S	Fast Repetitive Pulse Settling Parameters (50 $\Omega$ )	At Cost
65400S	Pulse Time Delay Interval	At Cost
65500S	Peak-to-Peak Detector Calibration at One Frequency Selected from Those Given in Table 9.23 at 1.2 V	At Cost
65501S	Additional Frequency for Peak-to-Peak Detector in 65500S	At Cost

## CHAPTER 10

### TIME AND FREQUENCY MEASUREMENTS

#### A. Broadcast and Measurement Services

<b><u>Technical Contacts:</u></b>	<b><u>Telephone:</u></b>	<b><u>Email:</u></b>	<b><u>Mailing Address:</u></b>
Michael A. Lombardi (Frequency)	(303) 497-3212	lombardi@boulder.nist.gov	NIST
Marc A. Weiss (Time)	(303) 497-3261	mweiss@boulder.nist.gov	325 Broadway, MC 847.40
John Lowe	(303) 497-5453	lowe@boulder.nist.gov	Boulder, CO 80305-3328

**Administrative and Logistics:**

Trudi Peppler (303) 497-3338 tpeppler@boulder.nist.gov  
**Fax:** (303) 497-6461

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
	Broadcast Services (WWW, WWVH, WWVB, GOES, ACTS and NTS)	
76100S	Frequency Measurement Service (Frequency Delivered to User's Site)	Initial One-Time Fee \$1,500 Monthly Charge \$500
76110S	Global Time Service (Frequency and Time delivered to User's Site)	\$15,000 per year
76120S	Characterization of Global Positioning System (GPS) Satellite Receivers	At Cost

#### B. Calibration and Characterization of Oscillators and Amplifiers

<b><u>Technical Contacts:</u></b>	<b><u>Telephone:</u></b>	<b><u>Email:</u></b>	<b><u>Mailing Address:</u></b>
David Howe	(303) 497-3277	dhowe@boulder.nist.gov	NIST
James E. Gray	(303) 497-3209	jgray@boulder.nist.gov	325 Broadway, MC 847
			Boulder, CO 80305-3328

**Administrative and Logistics:**

Trudi Peppler (303) 497-3338 tpeppler@boulder.nist.gov  
**Fax:** (303) 497-6461

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
77100C	Oscillator Frequency Calibration	At Cost
77110C	Characterization of Atomic Frequency Standards	At Cost
77120C	Characterization of Oscillators: Time Domain	At Cost

77130C	Characterization of Oscillators and Amplifiers: Phase Noise in the Frequency Domain	At Cost
77131C	Characterization of Oscillators and Amplifiers: Amplitude Noise in the Frequency Domain	At Cost

**C. Test of PM/AM Noise Measurement Systems**

**Technical Contact:**

David Howe

**Telephone:**

(303) 497-3277

**Email:**

dhowe@boulder.nist.gov

**Mailing Address:**

NIST

325 Broadway, MC 847.30

Boulder, CO 80305-3328

**Administrative and Logistics:**

Trudi Peppler

(303) 497-3338

tpeppler@boulder.nist.gov

**Fax:** (303) 497-6461

**Do not ship instruments or standards to the mailing address. Contact the staff for the shipping address.**

Service ID Number	Description of Services	Fee (\$)
77135C	Tests of RF PM/AM Noise Measurement Systems: On-Site Tests	At Cost
77136C	Tests of Microwave PM/AM Noise Measurement Systems: On-Site Tests	At Cost
77140S	Special Time/Frequency Measurements: Oscillators and Other Components	At Cost

## **CHAPTER 11**

### **SEMINARS**

The following announcements concern notification of changes in services and information about future NIST Measurement Seminars. General policy question regarding NIST measurement services should be referred to the Calibration Program.

#### **NIST MEASUREMENT SEMINARS**

NIST holds seminars and workshops that provide advice and assistance on measurements and calibrations. This affords laboratories outside NIST and opportunity to learn how to make measurements consistent with national standards which NIST maintains. Participation is open to a limited number of people who have the appropriate education, work experience, and current profession in measurement and standards laboratory activities.

Each seminar lasts from one to five days and is devoted to lectures, group discussions, and laboratory demonstrations. A course may be cancelled if registration is insufficient. However, in the past, requests for enrollment have nearly always exceeded the numbers that could be accommodated.

Acceptance letters will be mailed no later than 4 weeks prior to the scheduled date of the course. Detailed information on schedules and housing will be included. Those accepted will be expected to study the assigned reading material before coming to the course and should be prepared to discuss their own experiences with related problems.

See the Weights and Measures Program web site [www.ts.nist.gov/ts/htdocs/230/235/calen103.htm](http://www.ts.nist.gov/ts/htdocs/230/235/calen103.htm) for the NCWM Calendar of Events for other training not listed here.

NIST offers conferences and workshops throughout the year. To see the latest listing go to [www.nist.gov/public\\_affairs/confpage/confutr.htm](http://www.nist.gov/public_affairs/confpage/confutr.htm) for Upcoming NIST Conferences.

## ALPHABETICAL CROSS-INDEX

### Item

### Service ID Numbers

#### **A**

Absolute pressure transducers .....	30010C-30011C
Accelerometers .....	24010C-24060S
Ac-dc thermal converters (to 1MHz) .....	53350C-53352C
Ac-dc watt-hour or var-hour meters .....	56110S-56210M
Ac voltage, high accuracy .....	53200S-53203S
Acoustic devices .....	25060S
Acoustic measurements .....	25010C-25070S
Activation detector dosimetry .....	44070C-44090C
Air navigation aids .....	55210S-55230S
Air-speed indicators .....	19010C-19040S
Alpha-particle-emitting solid sources .....	43030C-43050C
American Petroleum Institute gages .....	12010C
Anechoic chambers .....	25010C-25070S
Anemometers .....	19010C-19040S
Angle gage blocks .....	14010C
Angular measurements .....	14010C-14050S
Antenna parameter measurements, microwave .....	63100S-63400S
Attenuators, rf and microwave .....	61210S-61250S
Audio-frequency phase meter .....	55120C-55141C

#### **B**

Ball plates .....	11050S
Balls .....	11030S
Barometers .....	29035C, 30010C-30011C
Beckman thermometers .....	31180S
Bell provers .....	18010C
Beta-particle applications .....	47030C-47040S
Beta-particle emitting sources .....	43060S, 43070S,
.....	47030C-47040S
Blackbody sources .....	35090S
Bolometer units, rf and microwave .....	61110S-61138S

#### **C**

Calorimeter thermometers .....	31170S
Capacitance and inductance measurements, high frequency .....	52210S-52310S
Capacitance and inductance measurements, low frequency .....	52100S-52181C
Capacitive voltage dividers .....	54310S
Capacitors, dielectric .....	52130C
Capacitors, high frequency .....	52210S-52221S
Capacitors, low frequency .....	52110S-52171C
Capacitors, power frequency .....	52400C
Coaxial attenuators .....	61210S-61211S
Coaxial thermistor detectors .....	61110S-61153S
Color measuring instruments .....	37120S
Color temperature .....	37010C-37050S
Complex dimensional standards .....	12010C-12040S
Coordinate measuring machines .....	11050S, 12040S,



.....	15010C-15040C
-software algorithms .....	10070S-10082S
-socketed ball bars .....	SRMs (p. 5)
-probe performance spheres.....	SRMs (p. 5)
Cryogenic flow measurements .....	18800S
Cryogenic resistance thermometers.....	33355S
Current and voltage transformers .....	54510C-54600S

## ***D***

Dc resistance measurements .....	51100S-51163C
Dc voltage measurements .....	53110S-53190S
Deadweight piston gages .....	29010C
Density measurements, liquids .....	17040S
Detector standards, windowed photodiode.....	40560C-40561C
Detector standards, windowless photodiode.....	40510C
Detectors, IR.....	39080S
Detectors, near ultraviolet to soft x-ray region.....	40599S
Detectors, radiometric .....	39080S
Detectors, spectroradiometric .....	39071C-39090S
Detectors, used with lasers .....	42110C-42180S
Deuterium lamps .....	39050C
Dew-point hygrometer.....	36010C-36020C
Diameter measurements .....	11010S-11060S
Dielectric materials.....	61620S
Differential pressure transducers .....	30020C-30021C
Digital multimeters, low frequency .....	53200S-53203S
Dimensional metrology .....	10010C-14050S
Dividers, inductive .....	54110S-54131C
Dividers, resistive .....	54210C-54213S
Dosimeters, electron beam .....	48010M-48020S
Dosimeters, high dose .....	49010C-49050S
Dosimeters, neutron.....	44100S
Dosimeters, radiochromic.....	49010C-49030C
Dosimeters, x-ray, gamma-ray, and electron.....	46010C-48020S
Dosimetry, neutron .....	44010C-44100S

## ***E***

Earphones .....	25070S
Electromagnetic field-strength parameter measurements .....	64100S-64300S
Electrometers.....	46030S
Electron beam dosimetry .....	48010M-48020S
End standards .....	10050S
Energy and power measurements, low frequency .....	56110S-56210M

## ***F***

Ferrous-ferric dosimeters.....	48010M-48011M
Fiber optic power meters.....	42130C-42180S
Field strength measurements, electromagnetic.....	64100S-64300S
Filament lamps, ribbon.....	35050C-35060C, .....39010C-39030C
Filters, spectral transmittance.....	38010C-38040C
Fixed-point devices, thermometric.....	33360S
Flashing-light photometer.....	37110S
Flats, optical reference.....	13010S
Flow measurements, cryogenic.....	18800S
Flowrate meters, liquid and gas.....	18010C-18070S
Flux standards, luminous.....	37060S
Force transducers.....	23010C-23260S
Frequency and time measurement services.....	76100S-76110S
Frequency domain.....	77131C

## ***G***

Gage blocks.....	10010C
Gages, API.....	12010C
Gages, ionization.....	30034C-30038C
Gages, low pressure.....	30040S
Gages, molecular drag.....	30029C-30031C
Gages, piston.....	29010C-29020C
Gages, plug.....	11010S
Gages, plug and ring.....	12020S
Gages, pressure.....	29010C-29040S
Gages, ring.....	11040S
Gages, step.....	11060S
Gages, two dimensional.....	12030S
Gages, vacuum.....	30010C-30050S
Gamma-ray dosimeters.....	46010C-46021C
Gamma-ray emitting sources.....	43010C-43020C, .....47010C-47011C
Gas flowmeters.....	18010C, 18050S
Gear measuring wires.....	11020C
Germanium resistance thermometers.....	33142C
Global time service.....	76110S
Global positioning system satellite receivers.....	76120S
Grid plates.....	11050S

## ***H***

Heat flux sensors.....	35100S-35102C
Helium permeation leaks.....	30060S-30062S
High dose dosimetry.....	49010C-49050S
High-frequency standard capacitors and inductors.....	52210S-52310S
High-frequency standard resistors.....	51310S
High-vacuum gages.....	30029C-30038C
High-voltage resistors.....	51210C
Humidity measurements.....	36010C-36070S
Hydrocarbon liquid flow meters.....	18030C, 18070S
Hydrometers.....	16010C-16020S
Hygrometers.....	36010C-36070S

## I

Illuminance meters .....	37090S
Impedance measurements.....	52110S
Impulse spectrum amplitude.....	65100S
Impulse response of coaxial networks.....	65300S
Incandescent lamps.....	37060S
Indexing tables .....	14030S
Inductance and capacitance measurements, low frequency.....	52110S-52181C
Inductance and capacitance measurements, high frequency.....	52210S-52310S
Inductive voltage dividers .....	54110S-54131C
Industrial grade thermometers .....	31010C-37020S
Intensity, luminous .....	37010C-37020S
Interferometry.....	10010C
Internal diameter standards.....	11040S
Ionization chambers.....	47036C
Ionization gages.....	30034C-30038C
Irradiance detectors .....	39100S
Irradiance sources .....	39040C-39050C

## L

Laboratory thermometers .....	31010C-31180S
Lamps, deuterium arc .....	39050C
Lamps, incandescent.....	37060S
Lamps, quartz halogen.....	39040C-39045C
Lamps, ribbon filament .....	35050C-35060C
.....	39010C-39030C
Laser frequency/wavelength.....	14510S
Laser power and energy measurements .....	42110C-42180S
Leak artifacts .....	30060S-30062S
Length and diameter .....	11050S
Length measurements .....	10010C-10060S
Length standards.....	10050S
Light emitting diodes (LEDs).....	37130S
Line standards.....	10020C
Linearity of optical fiber power meters .....	42166C-42167S
Liquid flow meters .....	18020C,18060S
Liquid-in-glass thermometers.....	31010C-31180S
Load cells .....	23010C-23260S
Luminous flux .....	37060S
Luminous intensity .....	37010C-37020S
Luminous intensity of LEDs.....	37130S

## M

Mammography x-ray measuring instruments .....	46010C-46050S
Manometers .....	29035C
Mass measurements.....	22010C-22170S

### MEASUREMENT ASSURANCE PROGRAMS (MAPs)

Dc resistance.....	51110M
Dose interpretation of ferrous-ferric dosimeters.....	48010M-48011M
Laser power and energy.....	42120M, 42140M, 42150M
Platinum resistance thermometry .....	33370M-33380M
Watt-hour meters .....	56210M

Mercury-in-glass thermometers.....	31010C-31180S
Meteorological airspeed instrumentation .....	19030S
Meters, laser power and energy .....	42110C, 42170S
Meters, optical fiber power.....	42130C, 42140M, 42190S
Meters, phase.....	55110S-55141C
Microphones, pressure and free-field response .....	25010C-25050C
Micropotentiometers, low voltage .....	53201S
Micropotentiometers, rf .....	53350S-53352S
Microwave antenna parameter measurements .....	63100S-63400S
Molecular drag gages .....	30029C-30031C

## *N*

Neutron dosimeters.....	44100S
Neutron sources .....	44010C-44020C
Noise temperature measurements, coaxial and waveguide.....	61410S-61495S
Non-mercurial barometers and manometers.....	29035C

## *O*

Oil gaging and surveying tapes .....	10030C
Opal glass luminance standards.....	37070C
Optical fiber power meters .....	42130C, 42140M, 42180S
Optical flats .....	13010S
Optical polygons.....	14020S
Optical pyrometers .....	35010C-35040C
Optical reference planes .....	13010S
Optoelectronic Frequency Response .....	42155C
Oscillator characterization.....	77100C-77140S

## *P*

Penetrameters, x-ray .....	46040S
Personnel protection instrumentation .....	44060C
Phase measurements.....	55110S-55141C
Phase shifters, rf and microwave.....	61295S-61297S
Photodiode, spectral response.....	39070C
Photodiode, ultraviolet to near-infrared.....	39077C
Photodiodes, windowed and windowless .....	40510C-40560C
Photographic step tablets.....	38120C-38130C
Photometers .....	37090S
Photometric tests .....	37100S
Photometry .....	37010C-37110S
Photon Beams.....	49010C-49050S
Pickup sensitivity .....	24010C-24030C, 24050C
Piston gages, controlled clearance.....	29020C
Piston gages, dead weight.....	29010C
Piston gauges versus UIM.....	30025C
Pitot-static tubes .....	19010C
Platinum resistance thermometers .....	33010C-33310C
Plug and ring gages .....	12010C-12020C
Plug gages .....	11010S
PM/AM noise measurement systems .....	77135C-77136S
Pneumatic bridge hygrometers .....	36060C
Polygons, optical .....	14020S

Power and energy measurements, low frequency.....	56110S-56210M
Power meters, optical fiber.....	42130C-42140M, 42180S
Power meters, thermoelectric .....	61110S-61155S
Pressure gages and transducers.....	29030C
Pressure gages, low absolute .....	30010C-30011C
Pressure gages, low differential.....	30020C-30021C
Pressure gages, special tests .....	29040S
Pressure measurements.....	29010C-29040S,
.....	30010C-30062C
Proving rings .....	23010C-23260S
Pulse waveform measurements .....	65100S-65400S
Pyrometer indicators.....	32100C
Pyrometers, optical .....	35010C-35040C
Pyrometers, radiation.....	35070S-35072C

## **Q**

Q-standards.....	52710C-52711C
Quartz halogen lamps .....	39040C-39045C

## **R**

Radiance standard sources.....	39010C-39030C
Radiance thermometry.....	35010C-35084C
Radiant energy detectors .....	39070C
Radiation detectors .....	46010C-46011C
Radiation pyrometers.....	35070S
Radiation thermometry.....	35010C-35084C
Radioactive sources, alpha emitting .....	43030C-43050C, 43090S
Radioactive sources, beta emitting .....	43060S-43070S
Radioactive sources, gamma emitting .....	43010C-43020C
Radioactive sources, neutron emitting.....	44010C-44020C
Radiochrometric dosimeters .....	49020C-49030C
Radiometric detectors .....	39080S
Radiometric measurements .....	39010C-39080S,
.....	40510C-40599S
Radiometric sources .....	39060S
Radionuclides .....	43010S-43090S
Reflection coefficients, coaxial and waveguide terminals.....	61310S-61350S
Resistance measurements, dc .....	51100S-51163C
Resistance thermometers .....	33010C-33310C
Resistive voltage dividers.....	54210C-54213S
Resistors, high frequency .....	51310S
Resistors, high-precision standard, dc .....	51130C-51154C
Resistors, high voltage.....	51210C
Resistors, megohm .....	51142C-51154C
Resistors for current measurements.....	51160C-51163C
Ring gages .....	11040S
R-meters .....	46010C-46011C
Rods, surveying leveling .....	10040S
Rotary and indexing tables .....	14030S
Roughness calibration standards .....	15010C-15040S
Roundness measurements.....	13020S-13030S

## S

Saturated standard cells .....	53130C-53131C
Shock measurements .....	24040S
Sieves, special tests .....	10060S also SRMs (p. 5)
Spectral irradiance .....	39040C-39050C,
Spectral irradiance, lamps .....	39040C-39050C
Spectral radiance .....	39010C-39030C
Spectral radiance, lamps .....	39010C-39030C
Spectral reflectance .....	38060S
Spectral response, lasers .....	42164C
Spectral response, photodiode .....	39081S
Spectral transmittance filters .....	38010C-38040C, 38061S
.....	Also SRMs (p. 5)
Spectroradiometric detectors .....	39071C-39090S
Spectroradiometric sources .....	39010C-39060S
Specular gloss .....	38090S
Spherical diameter standards, balls .....	11030S
Stage micrometer .....	10020C
Standard voltage cells .....	53130C-53150C
Step gages, length .....	11060S
Step height measurements, surface .....	15030C
Step tablet density, photographic .....	38120C-38130C
Sucker rods .....	12010C
Surface color .....	38091S
Surface roughness standards .....	15040S
Surveying and oil gaging tapes .....	10030C
Surveying leveling rods .....	10040S

## T

Tapes .....	10030C
Thermal voltage converters (to 1 MHz) .....	53350C-53352C
Thermistor mounts .....	61110S-61155S
Thermocouples and thermocouple materials .....	32010C-32150S
Thermometers, Beckmann .....	31180S
Thermometer, calorimetric type .....	31170S
Thermometers, cryogenic type .....	33140C-33141C
Thermometers, germanium resistance .....	33142C
Thermometers, laboratory .....	31010C-31260S
Thermometers, platinum resistance .....	33010C-33310C
Thermometer, rhodium-iron resistance .....	33140C-33141C
Thermometric fixed-point devices .....	33360S also SRMs (p. 5)
Thermometry, radiance .....	35010C-35070S
Thread measuring wires .....	11020C
Threaded plug and ring gages .....	12020S
Time and frequency measurement services .....	76100S-76120C
Topography .....	15040S
Transducer sensitivity .....	24010C-24030C, 24050C
Transducers, low pressure .....	30010C-30021C
Transformers, voltage and current .....	54510C-54600S
Transmittance filters, spectral .....	38010C-38040C
Transmitting diffusers .....	37080S
Tungsten lamps .....	39010C-39046C
Tungsten strip lamps .....	35050C-35061C
Two-dimensional gages .....	12030S

## *U*

Ultraviolet detectors .....	40510C-40599S
Unsaturated standard cells .....	53150C

## *V*

Vacuum gages .....	30029C-30038C, 30050S
Vacuum measurements .....	30010C-30050S
Var, varhour meters .....	56200C-56202C
Very-high-frequency omnidirectional measurements .....	55210C-55230S
Vibration and shock measurements .....	24010C-24060S
Voltage, ac .....	53201S
Voltage, dc .....	53110S-53190S
Voltage, rf dc .....	53350S-53352S
Voltage and current transformers .....	54510C-54600S
Voltage dividers, capacitive .....	54310S
Voltage dividers, inductive .....	54110S-54131C
Voltage dividers, resistive .....	54210C-54213S
Voltage reference standards, solid state .....	53160C-53161C
Voltmeters, high accuracy, ac .....	53200S
Volume standards .....	17010C-17040S
VOR measurements .....	55110S

## *W*

Water flow meters .....	18020C, 18060S
Watt, watthour meters .....	56110S-56210M
Wattmeters, high power .....	61160S, 61190S
Wattmeters, high power .....	61160S, 61190S
Waveform measurements, pulse .....	65100S-65400S
Waveguide attenuators .....	61230S
Waveguide terminations and reflection coefficients .....	61330S-61350S
Waveguide thermistor detectors .....	61144S-61155S
Wavelength standards .....	38050C-38051C
Wedges .....	14040S
Weights (mass standards) .....	22010C-22170S
Wires for thread and gear measurements .....	11020C

## ***X***

X-ray and photographic step tablets .....	38100C-38130C
X-ray dosimeters .....	46010C-46050S
X-ray penetrameters .....	46040S